
SmartCode

H U T T O , T E X A S

JUNE 2014



SMARTCODE TABLE OF CONTENTS

Hutto, Texas

5.12 SIGNAGE STANDARDS

ARTICLE 1. GENERAL TO ALL PLANS		ARTICLE 6.	STANDARDS AND TABLES
1.1	AUTHORITY	TABLE 1	TRANSECT ZONE DESCRIPTIONS
1.2	APPLICABILITY	TABLE 1A	OLD TOWN TRANSECT ZONE
1.3	INTENT	TABLE 1A	DESCRIPTIONS
1.4	PROCESS	TABLE 3A	VEHICULAR LANE DIMENSIONS
1.5	WARRANTS AND VARIANCES	TABLE 4A	PUBLIC FRONTAGES - GENERAL
1.6	INCENTIVES	TABLE 4B	PUBLIC FRONTAGES - SPECIFIC
	E 2. [RESERVED]	TABLE 4C	THOROUGHFARE ASSEMBLIES
	E 3. NEW COMMUNITY PLANS	TABLE 5	[RESERVED]
3.1	INSTRUCTIONS	TABLE 6	PUBLIC PLANTING
3.2	SEQUENCE OF COMMUNITY DESIGN	TABLE 7	PRIVATE FRONTAGES
3.3	COMMUNITY UNIT TYPES	TABLE 8	BUILDING CONFIGURATION
3.4	TRANSECT ZONES	TABLE 9	
3.5	CIVIC ZONES	TABLE 10	BUILDING FUNCTION & ARKING
3.6	SPECIAL DISTRICTS	TABLE 11	PARKING CALCULATIONS
3.7	THOROUGHFARE STANDARDS	TABLE 12	SPECIFIC FUNCTION & USE
3.8	DENSITY CALCULATIONS		A SPECIFIC FUNCTION & USE: OLD TOWN
3.9	SPECIAL REQUIREMENTS	TABLE 13	CIVIC SPACE
	E 4. INFILL SCALE PLANS	TABLE 14	SMARTCODE SUMMARY
4.1	INSTRUCTIONS		A SMARTCODE SUMMARY: OLD TOWN
4.2	OLD TOWN REGULATING PLAN	TABLE 15A	A FORM-BASED CODE GRAPHICS-T3
4.3	TRANSECT ZONES	TABLE 15E	FORM-BASED CODE GRAPHICS-T4
4.4	CIVIC ZONES		C FORM-BASED CODE GRAPHICS-T5
4.5	SPECIAL DISTRICTS	TABLE 150	FORM-BASED CODE GRAPHICS-OT-3
4.6	PRE-EXISTING CONDITIONS	TABLE 15E	FORM-BASED CODE GRAPHICS-OT-4R
4.7	SPECIAL REQUIREMENTS		FORM-BASED CODE GRAPHICS-OT-4T
4.8	THOROUGHFARE STANDARDS	TABLE 150	FORM-BASED CODE GRAPHICS-OT-5H
	5. BUILDING SCALE PLANS	TABLE 15H	FORM-BASED CODE GRAPHICS-OT-5C
5.1	INSTRUCTIONS		FORM-BASED CODE GRAPHICS-SD-A
5.2	PRE-EXISTING CONDITIONS	TABLE 16A	A SUSTAINABILITY-WIND POWER
5.3	SPECIAL REQUIREMENTS	TABLE 16E	3 SUSTAINABILITY-SOLAR ENERGY
5.4	CIVIC ZONES		C SUSTAINABILITY-FOOD PRODUCTION
5.5	SPECIFIC TO T1 NATURAL ZONE		O SUSTAINABILITY-COMPOSTING AND
5.6	BUILDING DISPOSITION		RECYCLING
5.7	BUILDING CONFIGURATION	TABLE 16E	E LIGHT IMPRINT STORM DRAINAGE
5.8	BUILDING FUNCTION		MATRIX
5.9	PARKING AND DENSITY CALCULATIONS	TABLE 17	DEFINITIONS ILLUSTRATED
	PARKING LOCATION STANDARDS		DEFINITIONS
5.11	LANDSCAPE STANDARDS		

[BLANK PAGE]

SC2 Revised June 2014

1.1 AUTHORITY

1.1.1 The regulations contained in this section have been made in accordance with a comprehensive plan for the purpose of promoting health, safety, morals and the general welfare of the city. They have been designed to lessen the congestion in the Streets; to secure safety from fire, panic and other dangers; to provide adequate light and air; to prevent the overcrowding of land; to avoid undue concentration of population; to facilitate the adequate provision of transportation, water, sewerage, schools, parks and other public requirements. They have been made with reasonable consideration, among other things, for the character of the district and its peculiar suitability for particular uses, and with a view to conserving the value of buildings and encouraging the most appropriate use of the land throughout the city.

1.2 APPLICABILITY

- 1.2.1 The provisions of this section, when in conflict, shall take precedence over other sections of the Hutto Code of Ordinances outside of this Unified Development code (UDC).
- 1.2.2 Other provisions of the UDC shall continue to be applicable to issues not covered by this section except where those provisions would be in conflict with the Intent section below.

1.3 INTENT

The intent and purpose of this section is to enable, encourage and qualify the implementation of the following policies:

1.3.1 THE REGION

- a. That the region should retain its natural infrastructure and visual character derived from topography, woodlands, farmlands, and riparian corridors.
- b. That growth strategies should encourage Infill and redevelopment in parity with New Communities.
- c. That development which is non-contiguous to urban areas should be organized in the pattern of Clustered Land Development, Traditional Neighborhood Development (TND), or Regional Center Development (RCD).
- d. That Affordable Housing should be distributed throughout the region to match job opportunities and to avoid concentrations of poverty.
- e. That transportation Corridors should be planned and reserved in coordination with land use.
- f. That Green Corridors should be used to define and connect the Urbanized areas.
- g. That the region should include a framework of transit, pedestrian, and bicycle systems that provide alternatives to the automobile.
- h. That the revitalization of Old Town Hutto into a vibrant downtown that Is the center of community life In Hutto should be an important priority.

1.3.2 THE COMMUNITY

- a. That TNDs and Regional Centers should be compact, pedestrian-oriented and Mixed-Use.
- b. That TNDs and Regional Centers should be the preferred pattern of development and that Districts specializing in a single use should be the exception.
- c. That ordinary activities of daily living should occur within walking distance of most dwellings, allowing independence to those who do not drive.
- d. That interconnected networks of Thoroughfares should be designed to disperse traffic and reduce the length of automobile trips.
- e. That within neighborhoods, a range of housing types and price levels should be provided to accommodate diverse ages and incomes.
- f. That appropriate building Densities and land uses should be provided within walking distance of transit stops.
- g. That Civic, institutional, and Commercial activity should be embedded in downtowns, not isolated in remote single-use complexes.
- h. That schools should be sized and located to enable children to walk or bicycle to them.

i. That a range of Open Space including Parks, Squares, and playgrounds should be distributed within neighborhoods and downtowns.

1.3.3 THE BLOCK AND THE BUILDING

- a. That buildings and landscaping should contribute to the physical definition of Thoroughfares as Civic places.
- b. That development should adequately accommodate automobiles while respecting the pedestrian and the spatial form of public areas.
- c. That the design of Streets and buildings should reinforce safe environments, but not at the expense of accessibility.
- d. That architecture and landscape design should grow from local climate, topography, history, and building practice.
- e. That buildings should provide their inhabitants with a clear sense of geography and climate through energy efficient methods.
- f. That Civic Buildings and public gathering places should be provided as locations that reinforce community identity and support self-government.
- g. That Civic Buildings should be distinctive and appropriate to a role more important than the other buildings that constitute the fabric of the city.
- h. That the preservation and renewal of historic buildings should be facilitated, to affirm the continuity and evolution of society.
- i. That the harmonious and orderly evolution of urban areas should be secured through form-based codes.

1.3.4 THE TRANSECT

- a. That Communities should provide meaningful choices in living arrangements as manifested by distinct physical environments.
- b. That the Transect Zone descriptions on Table 1 shall constitute the Intent of this Code with regard to the general character of each of these environments.
- c. That the Transect Zone descriptions in Table 1A shall constitute the Intent of this Code with regard to the general character of Old Town Hutto environments.

1.4 PROCESS

- 1.4.1 Hutto hereby creates a Development Review Committee (DRC) comprised of City Planners, City Engineer, Public Works Director, Development Services Director, Planning Manager, Parks Director, Police Representative and Building Inspector. The DRC shall administratively review and process applications and plans for proposed projects for compliance with the provisions of this Code.
- 1.4.2 The Transect Zones shall be determined through a process of public hearing with approval by the City Council. Once these zones have been incorporated into this Code, then projects that require no Variances or Warrants, or only Warrants, shall be processed administratively without further Council approval.
- 1.4.3 With the exception of the Old Town (OT) Transect Zones, an applicant may appeal a decision of the DRC to the City Council. In OT Transect Zones, appeals of any decision of the DRC shall be made to the Historic Preservation Commission (HPC). An applicant may appeal a decision of the HPC to the City Council.
- 1.4.4 Should a violation of an approved Regulating Plan occur during construction, or should any construction, site work, or development be commenced without an approved Regulating Plan, the Development Services Department has the right to require the owner to stop, remove, and/or mitigate the violation, or to require the owner to secure a Variance to cover the violation.

1.5 WARRANTS AND VARIANCES

1.5.1 For purposes of a SmartCode District only, there shall be two types of deviation from the requirements of this Code: Warrants and Variances. Whether a deviation requires a Warrant or Variance shall be determined by the Development Services Department. The Development Services Department shall establish administrative guidelines for making this determination. These administrative guidelines shall be

SC4 Revised June 2014

- approved by the City Council.
- 1.5.2 A Warrant is a ruling that would permit a practice that is not consistent with a specific provision of this Code but is justified by the provisions of the Intent section above. With the exception of OT Transect Zones, the Development Services Department shall have the authority to approve or disapprove administratively a request for a Warrant pursuant to regulations established by the Development Services Department and approved by the City Council. Where no specific criteria for granting of the modification are specified, a Warrant may be granted only for a dimensional deviation of less than 10% of the specified standard.
- 1.5.3 A Variance allows a modification of a requirement under this Code, provided that the modification is not contrary to the public interest and, due to special conditions, a literal enforcement of the ordinance would result in unnecessary hardship, and so that the spirit of the ordinance is observed and substantial justice is done. "Unnecessary hardship" means a hardship by reason of exceptional shape of a Lot, exceptional topographic conditions, or other exceptional physical conditions of a parcel of land. Unnecessary hardship shall not include personal or financial hardship or any other hardship that is self-imposed. Requests for Variances shall be heard by the Zoning Board of Adjustment (ZBA) in accordance with the provisions of this UDC.
- 1.5.4 The request for a Warrant or Variance shall not subject the entire application to public hearing, but only that portion necessary to rule on the specific issue requiring the relief.
- 1.5.5 The following standards and requirements shall not be available for Warrants:
 - a. The maximum dimensions of traffic lanes.
 - b. The required provision of Rear Alleys and Rear Lanes.
 - c. The minimum Base Residential Densities.
 - d. The permission to build Accessory Buildings.
- 1.5.6 In OT Transect Zones, the HPC shall have the authority to approve or disapprove a request for a Warrant. The DRC shall evaluate the Warrant request pursuant to criteria established by the Development Services Department and approved by the City Council and forward a recommendation to the HPC. The criteria for granting a Warrant in any Transect Zone shall be based on the extent to which the application meets the vision and policy recommendations in the Old Town Master Plan.
- 1.5.7 Warrant requests are evaluated using the following criteria:
 - a. The proposed Function and use will not generate traffic levels that are higher than the adjacent roadways are designed for, and;
 - b. The proposed Function and use will not disturb nearby uses with excessive noise, lighting, or obnoxious odors, and;
 - c. For new construction and redevelopment, the Density level and scale of proposed Function and use will not conflict with that of the surrounding area, and;
 - d. If applicable, the form of the proposed Function and use meets the Intent, goals, and policies of the SmartCode, Heart of Hutto Master Plan, and Architectural Design Standards (Old Town only), and;
 - e. If a contributing structure or new construction in Old Town, the HPC has reviewed and issued a Certificate of Appropriateness, or is scheduled for such action.

1.6 INCENTIVES

- 1.6.1 Applications that are not subject to the mandatory provisions of this Code shall be eligible to utilize the following incentives By Right:
 - a. Applications under this Code shall receive priority review status by the DRC, ZBA, Planning and Zoning Commission, and City Council ahead of other applications that were eligible to use this Code but elected not to do so.
 - b. Applications under this Code shall be processed with priority over those under the existing conventional zoning code, including those with earlier filing dates.
 - c. The City shall waive the traffic impact analysis.

- d. Applications under this Code shall receive 50% off the cost of building permit fees.e. [Reserved for additional incentives]

SC6 Revised June 2014

[RESERVED]

[RESERVED]

SC8 Revised June 2014

3.1 INSTRUCTIONS

- 3.1.1 For land areas containing a minimum of 30 contiguous acres, the provisions of this section shall be available By Right, upon request by the developer. If the land areas requested for use under this Code are not currently zoned as a Community Planning Area under this Code, then the developer shall not be eligible to use this Code until the land has been rezoned for this Code. This rezoning shall be subject to the same requirements as any rezoning within this jurisdiction.
- 3.1.2 New Community Plans may be prepared in the absence of a Regional Plan or Comprehensive Plan by approval of the City Council.
- 3.1.3 Once the DRC or City Council approves a New Community Plan, the parcel shall become a Community Planning Area and shall be marked as such on the Zoning Map of Hutto. Within the Community Planning Area, this Code shall be the exclusive and mandatory regulation, and its provisions shall be applied in their entirety.
- 3.1.4 New Community Plans submitted in accordance with the provisions of this Code, and requiring no Variances, shall be approved administratively by the DRC.
- 3.1.5 New Community Plans may be prepared by an owner or by the Development Services Office.
- 3.1.6 New Community Plans shall include a Regulating Plan consisting of one or more maps showing the following, in compliance with the standards described in this section:
 - a. Transect Zones.
 - b. Civic Zones.
 - c. Thoroughfare network.
 - d. Special Districts, if any.
 - e. Special Requirements, if any.
 - f. Numbers of Warrants or Variances, if any.
- 3.1.7 New Community Plans shall include one set of preliminary site plans for each Transect Zone.

3.2 SEQUENCE OF COMMUNITY DESIGN

- 3.2.1 The site shall be structured using one or several Pedestrian Sheds, which should be located according to existing conditions, such as traffic intersections, adjacent developments, and natural features. The site or any Community Unit within it may be smaller or larger than its Pedestrian Shed.
- 3.2.2 The Pedestrian Sheds shall determine the approximate boundaries and centers of the Community types.
- 3.2.3 Transect Zones shall be allocated by Pedestrian Shed according to the applicable Community type.
- 3.2.4 Civic Zones shall be assigned according to Section 3.5.
- 3.2.5 Special Districts, if any, shall be assigned according to Section 3.6.
- 3.2.6 The Thoroughfare network shall be laid out according to Section 3.7.
- 3.2.7 Density shall be calculated according to Section 3.8.
- 3.2.8 Remnants of the site outside the Adjusted Pedestrian Shed(s) shall be assigned to Transect Zones or Civic Space by Warrant or Special District by Variance.

3.3 COMMUNITY UNIT TYPES

- 3.3.1 CLUSTERED LAND DEVELOPMENT (CLD)
 - a. A Clustered Land Development (CLD) shall be structured by one Standard Pedestrian Shed and shall consist of no fewer than 30 acres and no more than 80 acres.
 - b. A CLD shall include Transect Zones as allocated on Table 14. A minimum of 50% of the Community Unit shall be permanently allocated to a T1 Natural Zone and/or T2 Rural Zone.
- 3.3.2 TRADITIONAL NEIGHBORHOOD DEVELOPMENT (TND)
 - a. A Traditional Neighborhood Development (TND) shall be shall be structured by one Standard or Linear Pedestrian Shed and shall be no fewer than 80 acres and no more than 160 acres.
 - b. A TND shall include Transect Zones as allocated on Table 14.

- c. Larger sites shall be designed and developed as multiple Communities, each subject to the individual Transect Zone requirements for its type as allocated on Table 14. The simultaneous planning of adjacent parcels is encouraged.
- 3.3.3 REGIONAL CENTER DEVELOPMENT (RCD)
 - a. A Regional Center Development (RCD) shall be shall be structured by one Long Pedestrian Shed or Linear Pedestrian Shed and shall consist of no fewer than 80 acres and no more than 640 acres.
 - b. An RCD shall include Transect Zones as allocated on Table 14.
 - c. For larger sites, an RCD may be adjoined without buffer by one or more TNDs, each subject to the individual Transect Zone requirements for TND as allocated on Table 14. The simultaneous planning of adjacent parcels is encouraged.
- 3.3.4 TRANSIT ORIENTED DEVELOPMENT (TOD)
 - a. Any TND or RCD on an existing or projected rail or Bus Rapid Transit (BRT) network may be redesignated in whole or in part as TOD and permitted the higher Density represented by the Effective Parking allowance.
 - b. The use of a TOD overlay requires approval by Variance.
- 3.3.5 OTHER
 - a. Alternative Transect allocations that do not meet the percentages identified in Table 14 may be considered by the Planning and Zoning Commission for approval.
- 3.4 TRANSECT ZONES
- 3.4.1 Transect Zones shall be assigned and mapped on each New Community Plan according to the percentages allocated on Table 14.
- 3.4.2 A Transect Zone may include any of the elements indicated for its T-zone number throughout this Code, in accordance with Intent described in Table 1 and the metric standards summarized in Table 14.
- 3.5 CIVIC ZONES
- 3.5.1 GENERAL
 - a. Civic Zones dedicated for public use shall be required for each Community Unit and designated on the New Community Plan as Civic Space (CS) and Civic Building (CB).
 - b. Civic Space Zones are public sites permanently dedicated to Open Space.
 - c. Civic Building Zones are sites dedicated for buildings generally operated by not-for-profit organizations dedicated to culture, education, religion, government, transit and municipal parking, or for a use approved by the City Council.
 - d. A Civic Zone may be permitted by Warrant if it does not occupy more than 20% of a Pedestrian Shed, otherwise it is subject to the creation of a Special District.
 - e. Parking for Civic Zones shall be determined by Warrant. Civic Parking lots may remain unpaved if graded, compacted and landscaped.
- 3.5.2 CIVIC ZONES SPECIFIC TO ZONES T1, T2
 - a. Civic Buildings and Civic Spaces within T1 Natural and T2 Rural Zones shall be permitted only by Warrant.
- 3.5.3 CIVIC SPACE (CS) SPECIFIC TO ZONES T3-T5
 - a. Each Pedestrian Shed shall assign at least 5% of its Urbanized area to Civic Space.
 - b. Civic Spaces shall be designed as generally described in Table 13, approved by Warrant, and distributed throughout Transect Zones as described in Table 14.
 - c. Each Pedestrian Shed shall contain at least one Main Civic Space. The Main Civic Space shall be within 800-feet of the geographic center of each Pedestrian Shed, unless topographic conditions, pre-existing Thoroughfare alignments or other circumstances prevent such location. A Main Civic Space shall conform to one of the types specified in Table 13b, 13c, or 13d.

SC10 Revised June 2014

- d. Within 1000-feet of every Lot in Residential use, a Civic Space designed and equipped as a playground shall be provided. A playground shall conform to Table 13e.
- e. Each Civic Space shall have a minimum of 50% of its perimeter Enfronting a Thoroughfare, except for playgrounds.
- f. Civic Spaces may be permitted within Special Districts by Warrant.
- g. Parks may be permitted in Transect Zones T4 and T5 by Warrant.
- 3.5.4 CIVIC BUILDINGS (CB) SPECIFIC TO ZONES T3-T5
 - a. The owner shall covenant to construct a Meeting Hall or a Third Place in proximity to the Main Civic Space of each Pedestrian Shed. Its corresponding Public Frontage shall be equipped with a shelter and bench for a transit stop.
 - b. One Civic Building Lot shall be reserved for an elementary school. It's area shall be a minimum of three (3) acres. The school site may be within any Transect Zone. The school may be a public, charter or private school. If the site Is not accepted or developed by a school within five years, it may be assigned another Civic use.
 - c. One Civic Building Lot suitable for a childcare building shall be reserved within each Pedestrian Shed. The owner or a homeowners' association or other community council may organize, fund and construct an appropriate building as the need arises.
 - d. Civic Building sites shall not occupy more than 20% of the area of each Pedestrian Shed.
 - e. Civic Building sites should be located within or adjacent to a Civic Space, or at the axial termination of a significant Thoroughfare.
 - f. Civic Buildings shall not be subject to the standards of Article 5. The particulars of their design shall be determined by Warrant.
 - g. Civic Buildings may be permitted within Special Districts by Warrant.

3.6 SPECIAL DISTRICTS

- 3.6.1 Special District designations shall be assigned to areas that, by their intrinsic size, Function, or Configuration, cannot conform to the requirements of any Transect Zone or combination of zones.
- 3.6.2 Special Districts that do not have provisions within this Code shall be governed by the standards of the pre-existing zoning.

3.7 THOROUGHFARE STANDARDS

- 3.7.1 GENERAL
 - a. Thoroughfares are intended for use by vehicular and pedestrian traffic and to provide access to Lots and Open Spaces.
 - b. Thoroughfares shall generally consist of vehicular lanes and Public Frontages.
 - c. Thoroughfares shall be designed in context with the urban form and desired Design Speed of the Transect Zones through which they pass. The Public Frontages of Thoroughfares that pass from one Transect Zone to another shall be adjusted accordingly or, alternatively, the Transect Zone may follow the alignment of the Thoroughfare to the depth of one Lot, retaining a single Public Frontage throughout its trajectory.
 - d. Within the most rural Zones (T1 and T2) pedestrian comfort shall be a secondary consideration of the Thoroughfare. Design conflict between vehicular and pedestrian generally shall be decided in favor of the vehicle. Within the more urban Transect Zones (T3 through T5) pedestrian comfort shall be a primary consideration of the Thoroughfare. Design conflict between vehicular and pedestrian movement generally shall be decided in favor of the pedestrian.
 - e. The Thoroughfare network shall be designed to define Blocks not exceeding the size prescribed in Table 14. The perimeter shall be measured as the sum of Lot Frontage Lines. Block perimeter at the edge of the development parcel shall be subject to approval by Warrant.

- f. All Thoroughfares shall terminate at other Thoroughfares, forming a network. Internal Thoroughfares shall connect wherever possible to those on adjacent sites. Cul-de-sacs shall be subject to approval by Warrant to accommodate specific site conditions only.
- g. Each Lot shall Enfront a vehicular Thoroughfare, except that 20% of the Lots within each Transect Zone may Enfront a Passage.
- h. Thoroughfares along a designated B-Grid may be exempted by Warrant from one or more of the specified Public Frontage or Private Frontage requirements. See Table 7.
- i. Standards for Paths (PT) and Bicycle Trails (BT) shall be approved by Warrant.
- j. The standards for Thoroughfares within Special Districts shall be determined by Variance.

3.7.2 VEHICULAR LANES

- a. Thoroughfares may include vehicular lanes in a variety of widths for parked and for moving vehicles, including bicycles. The standards for vehicular lanes shall be as shown in Table 3A.
- b. A bicycle network consisting of Bicycle Trails (BT), Bicycle Routes (BR) and Bicycle Lanes (BL) should be provided throughout in accordance with Table 14. The community bicycle network shall be connected to existing or proposed regional networks wherever possible.

3.7.3 PUBLIC FRONTAGES

- a. SPECIFIC TO ZONES T1, T2, T3, T4, T5
 - i. the Public Frontage contributes to the character of the Transect Zone, and includes the types of Sidewalk, Curb, Planter, bicycle facility, and street trees.
 - ii. Public Frontages shall be designed as shown in Table 4A and Table 4B and allocated within Transect Zones as specified in Table 14.
 - iii. within the Public Frontages, the prescribed types of Public Planting and Public Lighting shall be as shown in Table 4A, Table 4B and Table 6. The spacing may be adjusted by Warrant to accommodate specific site conditions.
- b. SPECIFIC TO ZONES T1, T2, T3
 - i. the Public Frontage shall include trees of various species, naturalistically clustered, as well as understory.
 - ii. the introduced landscape shall consist primarily of native species requiring minimal irrigation, fertilization and maintenance. Lawn shall be permitted only by Warrant.
- c. SPECIFIC TO ZONES T4, T5
 - i. the introduced landscape shall consist primarily of durable species tolerant of soil compaction.
 - ii. the following Thoroughfares shall require Shopfront, Shopfront and Awning or Shopfront and Gallery Frontage types:

CS-80-56

CS-60-36

- d. SPECIFIC TO ZONE T4
 - i. the Public Frontage shall include trees planted in a regularly-spaced Allee pattern of single or alternated species with shade canopies of a height that, at maturity, clears at least one Story.
- e. SPECIFIC TO ZONE T5
 - i. the Public Frontage shall include trees planted in a regularly-spaced Allee pattern of single species with shade canopies of a height that, at maturity, clears at least one Story. At Retail Frontages, the spacing of the trees may be irregular, to avoid visually obscuring the Shopfronts.

3.8 DENSITY CALCULATIONS

3.8.1 All areas of the New Community Plan site that are not part of the T-1 shall be considered cumulatively the Net Site Area. The Net Site Area shall be allocated to the various Transect Zones according to the parameters specified in Table 14.

SC12 Revised June 2014

- 3.8.2 Density shall be expressed in terms of housing units per acre as specified for the area of each Transect Zone by Table 14. For purposes of Density calculation, the Transect Zones include the Thoroughfares but not land assigned to Civic Zones.
- 3.8.3 Within the percentage range shown on Table 14 for Other Functions, the housing units specified on Table 14 shall be exchanged at the following rates:
 - a. For Lodging: 2 bedrooms for each unit of Net Site Area Density.
 - b. For Office or Retail: 1000-square feet for each unit of Net Site Area Density.
 - c. The number of units exchanged shall be subject to approval by Warrant.
- 3.8.4 The housing and Other Functions for each Transect Zone shall be subject to further adjustment at the building scale as limited by Table 10 and Table 11.

3.9 SPECIAL REQUIREMENTS

- 3.9.1 A New Community Plan may designate any of the following Special Requirements:
 - a. A differentiation of the Thoroughfares as A-Grid and B-Grid. Buildings along the A-Grid shall be held to the highest standard of this Code in support of pedestrian activity. Buildings along the B-Grid may be more readily considered for Warrants allowing automobile-oriented standards. The Frontages assigned to the B-Grid shall not exceed 30% of the total length of Frontages within a Pedestrian Shed.
 - b. Designations for Mandatory and/or Recommended Retail Frontage requiring or advising that a building provide a Shopfront at Sidewalk level along the entire length of its Private Frontage. The Shopfront shall be no less than 70% glazed in clear glass and shaded by an Awning overlapping the Sidewalk as generally illustrated in Table 7 and specified in Article 5. The first floor shall be confined to Office, Retail or Lodging use through the depth of the Second Layer. (Table 17d)
 - c. Designations for Mandatory and/or Recommended Gallery Frontage, requiring or advising that a building provide a permanent cover over the Sidewalk, either cantilevered or supported by columns. The Gallery Frontage designation may be combined with a Retail Frontage designation.
 - d. [Reserved]
 - e. A designation for Coordinated Frontage, requiring that the Public Frontage (Table 4A) and Private Frontage (Table 7) be coordinated as a single, coherent landscape and paving design.
 - f. Designations for Mandatory and/or Recommended Terminated Vista locations, requiring or advising that the building be provided with architectural articulation of a type and character that responds visually to the location, as approved by the DRC.
 - g. A designation for Cross Block Passages, requiring that a minimum 8-foot-wide pedestrian access be reserved between buildings.

3.10 NATURAL DRAINAGE STANDARDS

- 3.10.1 GENERAL TO ALL ZONES T1, T2, T3, T4, T5
 - a. Trees should be planted below the grade of the Sidewalk and the Street in structural cells with sufficient root space.
 - b. Rain Gardens and Bioswales should be installed to infiltrate runoff from parking lots, Thoroughfares, Plazas and other impervious surfaces.
 - c. Where vegetative solutions are not feasible, porous concrete or porous asphalt should be specified for Sidewalks, parking lots, and Plazas to infiltrate stormwater.
- 3.10.2 SPECIFIC TO ZONES T3, T4
 - a. Native plant perennial landscapes should replace turf grass where possible and be very diverse. They should be placed lower than walkways, not mounded up.

[BLANK PAGE]

SC14 Revised June 2014

4. 1 INSTRUCTIONS

- 4.1.1 Within the areas designated as Old Town and other redevelopment areas on the Official Zoning Map for the City of Hutto, the Development Services Department shall prepare, or have prepared on its behalf, Infill Regulating Plans to guide further development. Such plans shall be prepared in a process of public consultation subject to approval by the City Council.
- 4.1.2 Infill Regulating Plans shall regulate, at minimum, an area the size of the Pedestrian Shed commensurate with its Community type as listed below. The Development Services Department shall determine a Community type based on existing conditions and intended evolution in the plan area.
- 4.1.3 Infill Regulating Plans shall consist of one or more maps showing the following:
 - a. The outline(s) of the Pedestrian Shed(s) and the boundaries of the Community Unit(s)
 - b. Transect Zones and any Civic Zones within each Pedestrian Shed, assigned according to an analysis of existing conditions and future needs.
 - c. A Thoroughfare network, existing or planned (Table 3A, Table 4A, Table 4B, and Table 4C)
 - d. Any Special Districts (Section 4.5)
 - e. Any Special Requirements (Section 4.7)
 - f. A record of any Warrants or Variances.
- 4.1.4 Within any area subject to an approved Infill Regulating Plan, this Code becomes the exclusive and mandatory regulation. Property owners within the plan area may submit Building Scale Plans under this section in accordance with the provisions of this Code. Building Scale Plans requiring no Variances shall be approved administratively by the DRC.
- 4.1.5 The owner of a contiguous parcel 10 acres or more within an area subject to an Infill Regulating Plan may apply to prepare a Special Area Plan. In consultation with the Development Services Department, a Special Area Plan may assign new Transect Zones, Civic Zones, Thoroughfares, Special Districts (if any) and Special Requirements (if any) as provided in this Code, with appropriate transitions to abutting areas.

4.2 OLD TOWN REGULATING PLAN

- 4.2.1 The Regulating Plan for Old Town Hutto is hereby established under this article as an Infill Regulating Plan for the area designated as "Old Town Hutto."
- 4.2.2 The Old Town Regulating Plan shall exclusively direct the application of this Code within the boundaries established in the Old Town Regulating Plan. The Old Town Regulating Plan has been established to ensure that development and redevelopment within its boundaries are consistent with the Old Town Vision and Master Plan.
- 4.2.3 Amendments to the Old Town Regulating Plan and associated regulations shall be undertaken with public input and subject to approval by the City Council.

4.3 TRANSECT ZONES

- 4.3.1 Transect Zone standards for Infill Regulating Plans should be calibrated by means of a survey of exemplary existing and intended conditions, as identified in a process of public consultation and subject to the approval of the City Council. Metrics shall be recorded on Table 14 and Table 15D through 15I.
- 4.3.2 The Old Town Regulating Plan shall establish the following Transect Zones specifically calibrated for Old Town (See Table 1B for Transect Zone descriptions): OT-3, OT-4T, OT-4R, OT-5H, OT-5C, and Special Districts SD-A. The metrics for the Old Town Transect zones are established in Table 14.

4.4 CIVIC ZONES

- 4.4.1 GENERAL
 - a. Infill Plans should designate Civic Space Zones (CS) and Civic Building Zones (CB).
 - b. A Civic Zone may be permitted by Warrant if it does not occupy more than 20% of a Pedestrian Shed, otherwise it is subject to the creation of a Special District. See Section 4.5.
 - c. Parking provisions for Civic Zones shall be determined by Warrant.

4.4.2 CIVIC SPACE ZONES (CS)

a. Civic Spaces shall be generally designed as described in Table 13, their type determined by the surrounding or adjacent Transect Zone in a process of public consultation subject to the approval of the City Council.

4.4.3 CIVIC BUILDING ZONES (CB)

- a. Civic Buildings shall be permitted by Variance in any Transect Zone or by Warrant on Civic Zones reserved in the Infill Regulating Plan.
- b. Civic Buildings shall not be subject to the Requirements of Building Scale Plans. The particulars of their design shall be determined by Warrant.

4.4.4 OLD TOWN HUTTO CIVIC ZONES

- a. The Old Town Regulating Plan establishes the required Civic Space Zones (CS) and Civic Building Zones (CB).
- b. Civic Spaces shall be generally designed as described in Table 13, their type determined by the surrounding or adjacent Transect Zone in a process of public consultation subject to the approval of the City Council.
- c. Civic Buildings shall be permitted by Warrant in the OT-4R, OT-4T, OT-5H, OT-5C, and SD-A Transect Zones including the areas reserved for Civic Zones in the Old Town Regulating Plan.
- d. Civic Buildings shall not be subject to the requirements of Building Scale Plans (Article 5). The particulars of their design shall be determined by Warrant. Civic Buildings in Old Town shall be designed as feature buildings described in the Old Town Architectural Design Standards.

4.5 SPECIAL DISTRICTS

- 4.5.1 Areas that, by their intrinsic size, Function, or Configuration, cannot conform to the requirements of any Transect Zone or combination of Zones shall be designated as Special Districts by the Development Services Department in the process of preparing an Infill Plan.
- 4.5.2 Special Districts that do not have provisions within this Code shall be governed by the standards of the preexisting zoning.

4.6 PRE-EXISTING CONDITIONS

4.6.1 NON-CONFORMING BUILDINGS AND USES

- a. Regardless of transfer of ownership, existing Non-Conforming Buildings with a Non-Conforming Use that do not conform to the provisions of this Code may continue as they are until:
 - i. the building is reconstructed or Substantially Modified such that the collective reconstructions or modifications within any three (3) year period are valued at more than either \$50,000 or a total of 50% of the assessed value of the structure in the most recently certified tax rolls, whichever is greater; or
 - ii. any building facade on a designated A-Grid Street (per the Old Town Regulating Plan) is changed. These may include changes to facade colors, architectural elements, Sidewalks, windows, doors, or any other feature that alters that facade (excluding signage).
- b. Regardless of transfer of ownership, existing Non-Conforming Buildings that do not conform to the provisions of this Code may change use or Building Function within the same building, provided the new use or Building Function is permitted in Table 12A until:
 - i. the building is reconstructed or Substantially Modified such that the collective reconstructions or modifications within any three (3) year period are valued at more than either \$50,000 or a total of 50% of the assessed value of the structure in the most recently certified tax rolls, whichever is greater; or
 - ii. any building facade on a designated A-Grid Street (per the Old Town Regulating Plan) is changed. These may include changes to facade colors, architectural elements, Sidewalks, windows, doors, or any other feature that alters that facade (excluding signage).

SC16 Revised June 2014

- c. Regardless of transfer of ownership, existing Non-Conforming Buildings and Non-Conforming Uses that have lost their Non-Conforming status as determined by 10.206 of the UDC may continue or change use within the same building, provided the new use or Building Function is permitted in Table 12A, only with the approval of a Warrant by the HPC.
- d. Any Substantial reconstruction or Modification of or change to an A-Grid facade of a Non-Conforming Building shall meet the provisions of this Code unless a Warrant is granted by the HPC. In granting or denying a Warrant for such modifications, the HPC shall evaluate the extent to which the proposed modifications result in greater or lesser conformance with the specifications of this Code and the extent to which the modifications meet the vision and Intent of the Old Town Hutto Master Plan.
- 4.6.2 Where buildings exist on adjacent Lots, the DRC may require that a proposed building match one or the other of the adjacent Setbacks and heights or the average on the Block, rather than the provisions of this Code for the OT-3 and OT-4T zones.
- 4.6.3 The restoration or rehabilitation of an existing building shall not require the provision of on-site stormwater retention/detention in addition to that existing.
- 4.6.4 Regardless of the dollar value of modifications, all existing Non-Conforming single-family Residential buildings in the OT-3 zone are not required to meet the standards in this Code as long as they do not increase their Non-Conformity in any way. Any changes in building height or footprint will need to comply with this Code for the portions that are added or modified only.

4.7 SPECIAL REQUIREMENTS

- 4.7.1 An Infill Community Plan may designate any of the following Special Requirements:
 - a. A differentiation of the Thoroughfares as A-Grid and B-Grid. Buildings along the A-Grid shall be held to the highest standard of this Code in support of pedestrian activity. Buildings along the B-Grid may be more easily considered for Warrants allowing automobile-oriented standards. The Frontages assigned to the B-Grid shall not exceed 30% of the total length of Frontages within a Pedestrian Shed.
 - b. Designations for Mandatory and/or Recommended Retail Frontage requiring or advising that a building provide a Shopfront at Sidewalk level along the entire length of its Private Frontage. The Shopfront shall be no less than 70% glazed in clear glass and shaded by an Awning overlapping the Sidewalk as generally illustrated in Table 7 and specified under the Building Scale Plans provisions. The first floor shall be confined to Office, Retail or Lodging use through the depth of the Second Layer. (Table 17d.)
 - c. Designations for Mandatory and/or Recommended Gallery Frontage, requiring or advising that a building provide a permanent cover over the Sidewalk, either cantilevered or supported by columns. The Gallery Frontage designation may be combined with a Retail Frontage designation.
 - d. [Reserved]
 - e. A designation for Coordinated Frontage, requiring that the Public Frontage (Table 4A) and Private Frontage (Table 7) be coordinated as a single, coherent landscape and paving design.
 - f. Designations for Mandatory and/or Recommended Terminated Vista locations, requiring or advising that the building be provided with architectural articulation of a type and character that responds visually to the location, as approved by the DRC.
 - g. A designation for Cross Block Passages, requiring that a minimum 8-foot-wide pedestrian access be reserved between buildings.
- 4.7.2 The Old Town Regulating Plan designates the following Special Requirements:
 - a. The Old Town Regulating Plan Special Requirements shall establish all Thoroughfares in Old Town as A-Grid and B-Grid. Buildings along the A-Grid shall be held to the highest standard of this Code in support of pedestrian activity. Buildings along the B-Grid may be more readily considered for Warrants allowing automobile-oriented standards.
 - b. Designations for Required and Recommended Commercial Frontage requiring or advising that a building provide a Shopfront at Sidewalk level along the entire length of its Private Frontage. The glazing

requirements for Shopfronts shall be established by the Old Town Architectural Design Standards in Appendix A. An Awning overlapping the Sidewalk as generally illustrated in Table 7 and specified under the Building Scale Plans provisions shall be provided along Required Commercial Frontages. The first floor shall be confined to Office, Retail or Lodging use through the depth of the Second Layer. (Table 17d.)

 Designations for Required and Recommended Terminated Vista locations, requiring that the building be designed as a feature building as described in the Old Town Architectural Design Standards in Appendix A.

4.8 THOROUGHFARE STANDARDS

4.8.1 GENERAL

- a. Thoroughfares are intended for use by vehicular and pedestrian traffic and to provide access to Lots and Open Spaces.
- b. Thoroughfares shall generally consist of vehicular lanes and Public Frontages.
- c. Thoroughfares shall be designed in context with the urban form and desired Design Speed of the Transect Zones through which they pass. The Public Frontages of Thoroughfares that pass from one Transect Zone to another shall be adjusted accordingly or, alternatively, the Transect Zone may follow the alignment of the Thoroughfare to the depth of one Lot, retaining a single Public Frontage throughout its trajectory. Table 3A shall establish the Vehicular Lane Dimensions within Old Town Transect Zones. Table 4C shall establish permitted Thoroughfare Assemblies within Old Town.
- d. Within all the Old Town Transect Zones, pedestrian comfort shall be a primary consideration of the Thoroughfare. Design conflict between vehicular and pedestrian movement generally shall be decided in favor of the pedestrian.
- e. The Thoroughfare network shall be designed to define Blocks not exceeding the size prescribed in Table 14. The perimeter shall be measured as the sum of Lot Frontage Lines. Block perimeter at the edge of the development parcel shall be subject to approval by Warrant.
- f. All Thoroughfares shall terminate at other Thoroughfares, forming a network. Internal Thoroughfares shall connect wherever possible to those on adjacent sites. Cul-de-sacs shall be subject to approval by Warrant to accommodate specific site conditions only.
- g. Thoroughfares along a designated B-Grid may be exempted by Warrant from one or more of the specified Public Frontage or Private Frontage requirements. See Table 7.
- h. Standards for Paths (PT) and Bicycle Trails (BT) shall be approved by the Parks and Development Services Departments.
- i. Standards for Thoroughfares in SD-A zone shall be determined by the Development Services Department.

4.8.2 VEHICULAR LANES

- a. Thoroughfares may include vehicular lanes in a variety of widths for parked and for moving vehicles, including bicycles. The standards for vehicular lanes shall be as shown in Table 3A.
- b. A bicycle network consisting of Bicycle Trails (BT), Bicycle Routes (BR) and Bicycle Lanes (BL) should be provided throughout in accordance with Table 14. The community bicycle network shall be connected to existing or proposed regional networks wherever possible.

4.8.3 PUBLIC FRONTAGES

- a. GENERAL TO ALL ZONES OT-3, OT-4R, OT-4T, OT-5H, OT-5C, AND SPECIAL DISTRICT SD-A
 - i. the Public Frontage contributes to the character of the Transect Zone, and includes the types of Sidewalk, Curb, Planter, bicycle facility, and street trees.
 - ii. Public Frontages shall be designed as shown in Table 4A and Table 4B and allocated within Transect Zones as specified in Table 14.

SC18 Revised June 2014

- iii. within the Public Frontages, the prescribed types of Public Planting and Public Lighting shall be shown in Table 4A, Table 4B and Table 6. The spacing may be adjusted by Warrant to accommodate specific site conditions.
- b. SPECIFIC TO ZONE OT-3
 - i. the Public Frontage shall include trees of various species, naturalistically clustered, as well as understory.
 - ii. the introduced landscape shall consist primarily of native species requiring minimal irrigation, fertilization and maintenance. Lawn shall be permitted only by Warrant.
- C. SPECIFIC TO ZONES OT-4T, OT-4R, OT-5H, OT-5C, AND SPECIAL DISTRICT SD-A
 - i. the introduced landscape shall consist primarily of durable species tolerant of soil compaction.
- d. SPECIFIC TO ZONES OT-4T AND OT-4R
 - i. the Public Frontage shall include trees planted in a regularly-spaced Allee pattern of single or alternated species with shade canopies of a height that, at maturity, clears at least one Story.
- e. SPECIFIC TO ZONES OT-5H AND OT-5C
 - i. the Public Frontage shall include trees planted in a regularly-spaced Allee pattern of single species with shade canopies of a height that, at maturity, clears at least one Story. At Retail Frontages, the spacing of the trees may be irregular, to avoid visually obscuring the Shopfronts.

[BLANK PAGE]

SC20 Revised June 2014

5.1 INSTRUCTIONS

- 5.1.1 Lots and buildings located within the Old Town Regulating Plan or a New Community Plan or Infill Community Plan are subject to this section.
- 5.1.2 Owners and developers may have the design plans required under this Section prepared on their behalf. Such plans require administrative approval by the DRC.
- 5.1.3 Building and Site Plans shall show the following, in compliance with the standards described in this Section:
 - a. For preliminary site and building approval:
 - · Building Disposition
 - Building Configuration
 - Building Function
 - Parking Location Standards
 - Architectural Design Standards (for OT Transect Zones)
 - b. For final approval, in addition to the above:
 - Landscape Standards
 - Signage Standards
 - Special Requirements, if any
 - Architectural Design Standards

5.2 PRE-EXISTING CONDITIONS

- 5.2.1 SPECIFIC TO OLD TOWN TRANSECT ZONES
 - a. Regardless of transfer of ownership, existing Non-Conforming Buildings with a Non-Conforming Use that do not conform to the provisions of this Code may continue as they are until:
 - i. the building is reconstructed or Substantially Modified such that the collective reconstructions or modifications within any three (3) year period are valued at more than either \$50,000 or a total of 50% of the assessed value of the structure in the most recently certified tax rolls, whichever is greater; or
 - ii. any building facade on a designated A-Grid Street (per the Old Town Regulating Plan) is changed. These may include changes to facade colors, architectural elements, Sidewalks, windows, doors, or any other feature that alters that facade (excluding signage).
 - b. Regardless of transfer of ownership, existing Non-Conforming Buildings that do not conform to the provisions of this Code may change use or Building Function within the same building, provided the new use or Building Function is permitted in Table 12A until:
 - i. the building is reconstructed or Substantially Modified such that the collective reconstructions or modifications within any three (3) year period are valued at more than either \$50,000 or a total of 50% of the assessed value of the structure in the most recently certified tax rolls, whichever is greater; or
 - ii. any building facade on a designated A-Grid Street (per the Old Town Regulating Plan) is changed. These may include changes to facade colors, architectural elements, Sidewalks, windows, doors, or any other feature that alters that facade (excluding signage).
 - c. Regardless of transfer of ownership, existing Non-Conforming Buildings and Non-Conforming Uses that have lost their Non-Conforming status as determined by 10.206 of the UDC may continue or change use within the same building, provided the new use or Building Function is permitted in Table 12A, only with the approval of a Warrant by the HPC.
 - d. Any Substantial reconstruction or Modification of or change to an A-Grid facade of a Non-Conforming Building shall meet the provisions of this Code unless a Warrant is granted by the HPC. In granting or denying a Warrant for such modifications, the HPC shall evaluate the extent to which the proposed modifications result in greater or lesser conformance with the specifications of this Code and the extent to which the modifications meet the vision and Intent of the Old Town Hutto Master Plan.

- e. Where buildings exist on adjacent Lots, the DRC may require that a proposed building match one or the other of the adjacent Setbacks and heights or the average on the Block, rather than the provisions of this Code for the OT-3 and OT-4T zones.
- f. The restoration or rehabilitation of an existing building shall not require the provision of on-site stormwater retention/detention in addition to that existing.
- g. Regardless of the dollar value of modifications, all existing Non-Conforming single-family Residential buildings in the OT-3 zone are not required to meet the standards in this Code as long as they do not increase their non-conformity in any way. Any changes in building height or footprint will need to comply with this Code for the portions that are added or modified only.
- 5.2.2 GENERAL TO ALL OTHER TRANSECT ZONES (EXCEPT OLD TOWN ZONES)
 - a. Existing buildings and appurtenances that do not conform to the provisions of this Code may continue in use as they are until a Substantial Modification is requested, at which time the DRC shall determine the provisions of this Section that shall apply.
- 5.2.3 [RESERVED]
- 5.2.4 Where buildings exist on adjacent Lots, the DRC may require that a proposed building match one or the other of the adjacent Setbacks and heights or the average on the Block, rather than the provisions of this Code for T3.
- 5.2.5 [RESERVED]
- 5.2.6 The restoration or rehabilitation of an existing building shall not require the provision of (a) parking in addition to that existing nor (b) on-site stormwater retention/detention in addition to that existing. Existing parking requirements that exceed those for this Code may be reduced as provided by Table 10 and Table 11.

5.3 SPECIAL REQUIREMENTS

- 5.3.1 A New Community Plan or an Infill Community Plan may designate any of the following Special Requirements to be applied according to the standards of this section:
 - a. A differentiation of the Thoroughfares as A-Grid and B-Grid. Buildings along the A-Grid shall be held to the highest standard of this Code in support of pedestrian activity. Buildings along the B-Grid may be more readily considered for Warrants allowing automobile-oriented standards. The Frontages assigned to the B-Grid shall not exceed 30% of the total length of Frontages within a Pedestrian Shed.
 - b. Designations for Mandatory and/or Recommended Retail Frontage requiring or advising that a building provide a Shopfront at Sidewalk level along the entire length of its Private Frontage. The Shopfront shall be no less than 70% glazed in clear glass and shaded by an Awning overlapping the Sidewalk as generally illustrated in Table 7. The first floor shall be confined to Office, Retail or Lodging use through the depth of the Second Layer. (Table 17d.)
 - c. Designations for Mandatory or Recommended Gallery Frontage, requiring or advising that a building provide a permanent cover over the Sidewalk, either cantilevered or supported by columns. The Gallery Frontage designation may be combined with a Retail Frontage designation.
 - d. [Reserved]
 - e. A designation for Coordinated Frontage, requiring that the Public Frontage (Table 4A) and Private Frontage (Table 7) be coordinated as a single, coherent landscape and paving design.
 - f. Designations for Mandatory and/or Recommended Terminated Vista locations, requiring or advising that the building be provided with architectural articulation of a type and character that responds visually to the location, as approved by the DRC.
 - g. A designation for Cross Block Passages, requiring that a minimum 8-foot-wide pedestrian access be reserved between buildings.
- 5.3.2 The Old Town Regulating Plan designates the following Special Requirements:
 - a. The Old Town Regulating Plan Special Requirements shall establish Thoroughfares in Old Town as A-

SC22 Revised June 2014

- Grid and B-Grid. Buildings along the A-Grid shall be held to the highest standard of this Code in support of pedestrian activity. Buildings along the B-Grid may be more readily considered for Warrants allowing automobile-oriented standards.
- b. Designations for Required and Recommended Commercial Frontage requiring or advising that a building provide a Shopfront at Sidewalk level along the entire length of its Private Frontage. The glazing requirements for Shopfronts shall be established by the Old Town Architectural Design Standards in Appendix A. An Awning overlapping the Sidewalk as generally illustrated in Table 7 and specified under the Building Scale Plans provisions shall be provided along Required Commercial Frontages. The first floor shall be confined to Office, Retail or Lodging use through the depth of the Second Layer. (Table 17d.)
- c. Designations for Required and Recommended Terminated Vista locations, requiring that the building be designed as a feature building as described in the Old Town Architectural Design Standards in Appendix A

5.4 CIVIC ZONES

- 5.4.1 GENERAL
 - a. Civic Zones are designated on Community Plans as Civic Space (CS) or Civic Building (CB).
 - b. Parking provisions for Civic Zones shall be determined by Warrant.
- 5.4.2 CIVIC SPACES (CS)
 - a. Civic Spaces shall be generally designed as described in Table 13.
- 5.4.3 CIVIC BUILDINGS (CB)
 - a. Civic Buildings shall not be subject to the requirements of this Article. The particulars of their design shall be determined by Warrant.
- 5.4.4 OLD TOWN HUTTO CIVIC ZONES
 - a. The Old Town Regulating Plan Special Requirements establishes the required Civic Space Zones (CS) and Civic Building Zones (CB).
 - b. Civic Spaces shall be generally designed as described in Table 13, their type determined by the surrounding or adjacent Transect Zone in a process of public consultation subject to the approval of the City Council.
 - c. Civic Buildings shall be permitted by Warrant in the OT-4R, OT-4T, OT-5H, OT-5C and Special District SD-A Transect Zones including the areas reserved for Civic Zones in the Old Town Regulating Plan.
 - d. Civic Buildings shall not be subject to the requirements of this Code. The particulars of their design shall be determined by Warrant. Civic Buildings in Old Town shall be designed as feature buildings described in the Old Town Architectural Design Standards.

5.5 SPECIFIC TO T1 NATURAL ZONE

5.5.1 Buildings in the T1 Natural Zone are permitted only by Variance. Permission to build in T1 and the Building Scale Plan standards shall be determined concurrently as Variances, in public hearing of the ZBA. Once the ZBA has made a decision on this request that decision shall be subject to review by the City Council in a public hearing.

5.6 BUILDING DISPOSITION

- 5.6.1 SPECIFIC TO ZONE T2
 - a. Building Disposition shall be determined by Warrant.
- 5.6.2 SPECIFIC TO ZONES T3, T4, T5 AND ALL OT ZONES
 - a. Newly platted Lots shall be dimensioned according to Table 14, 14B-f and Table 15.
 - b. Building Disposition types shall be as shown in Table 9, Table 14 and 14B-i.
 - c. Buildings shall be disposed in relation to the boundaries of their Lots according to Table 14 and Table 15.
 - d. One Principal Building at the Frontage, and one Outbuilding to the rear of the Principal Building, may be

- built on each Lot as shown in Table 17c.
- e. Lot coverage by building shall not exceed that recorded in Table 14 and Table 15.
- f. Facades shall be built parallel to a rectilinear Principal Frontage Line or to the tangent of a curved Principal Frontage Line, and along a minimum percentage of the Frontage width at the Setback, as specified as Frontage Buildout on Table 14 and Table 15.
- g. Setbacks for Principal Buildings shall be as shown in Table 14 and Table 15. In the case of an Infill Lot, Setbacks shall match one of the existing adjacent Setbacks. Setbacks may otherwise be adjusted by Warrant.
- h. Rear Setbacks for Outbuildings shall be as shown in Table 14 and Table 15.
- i. To accommodate slopes over 10%, relief from front Setback requirements is available by Warrant.
- 5.6.3 SPECIFIC TO ZONE OT-3
 - a. [Reserved]
- 5.6.4 SPECIFIC TO ZONE OT-4R, OT-4T, OT-5H AND SPECIAL DISTRICT SD-A
 - a. The Principal Entrance shall be on a Frontage Line.
- 5.6.5 SPECIFIC TO ZONE T4 AND T5
 - a. Sideyard Dispositions shall have a 0-foot or 3-foot minimum side Setback.
- 5.6.6 SPECIFIC TO ZONE T5
 - a. Lot coverage in T5 may be calculated on the scale of the Block.
 - b. Shopfront Frontages must be paved.
- 5.7 BUILDING CONFIGURATION
- 5.7.1 GENERAL TO ZONES T2, T3, T4, T5
 - a. The Private Frontage of buildings shall conform to and be allocated in accordance with Table 7 and Table 14.
 - b. Buildings on corner Lots shall have two Private Frontages as shown in Table 17. Prescriptions for the Second and Third Layers pertain only to the Principal Frontage. Prescriptions for the First Layer pertain to both Frontages.
 - c. All Facades shall be glazed with clear glass no less than 30% of the first Story.
 - d. Building heights shall conform to Table 8 and Table 14.
 - e. Stories may not exceed 14-feet in height from finished floor to finished floor, except for a first floor Commercial Function, which shall be a minimum of 11-feet with a maximum of 25-feet. A single floor level exceeding 14-feet, or 25-feet at ground level, shall be counted as two stories. Mezzanines extending beyond 33% of the floor area shall be counted as an additional floor.
 - f. In a Parking Structure or garage, each above-ground level counts as a single Story regardless of its relationship to habitable Stories.
 - g. Height limits do not apply to Attics or raised basements, masts, belfries, clock towers, chimney flues, water tanks, or elevator bulkheads. Attics shall not exceed 14-feet in height.
- 5.7.2 [RESERVED]
- 5.7.3 SPECIFIC TO ZONES T3, OT-3
 - a. No portion of the Private Frontage may Encroach the Sidewalk.
 - b. Open porches may Encroach the First Layer 50% of its depth. (Table 17d)
 - c. Balconies and bay windows may Encroach the First Layer 25% of its depth except that balconies on porch roofs may Encroach as does the porch.
- 5.7.4 SPECIFIC TO ZONES T4, OT-4T, OT-4R
 - a. Balconies, open porches and bay windows may Encroach the First Layer 50% of its depth. (Table 17d)
 - b. Awnings may Encroach the Sidewalk to within 2-feet of the Curb but must clear the Sidewalk vertically by at least 8-feet.

SC24 Revised June 2014

5.7.5 SPECIFIC TO ZONE T5

- a. Awnings and Galleries may fully Encroach the Sidewalk to the Curb but must clear the Sidewalk vertically by at least 8-feet.
- b. Stoops, Lightwells, balconies, bay windows, and terraces may Encroach the First Layer 100% of its depth. Balconies and bay windows may Encroach the Sidewalk 25% of its depth. (Table 17d)
- c. Loading docks and service areas may be permitted on Frontages only by Warrant.
- d. In the absence of a building Facade along any part of a Frontage Line, a Streetscreen shall be built coplanar with the Facade.
- e. Streetscreens should be between 3.5 and 8-feet in height. The Streetscreen may be replaced by a hedge or fence by Warrant. Streetscreens shall have openings no larger than necessary to allow automobile and pedestrian access.
- f. A first level Residential or Lodging Function shall be raised a minimum of 12-inches from average Sidewalk grade.

5.7.6 SPECIFIC TO ZONES OT-3, OT-4R, OT-4T, OT-5H, OT-5C AND SPECIAL DISTRICT SD-A

- a. The Private Frontage of buildings shall conform to and be allocated in accordance with Table 7 and Table 14.
- b. Buildings on corner Lots shall have two Private Frontages as shown in Table 17. Prescriptions for the parking Layers pertain only to the Principal Frontage. Prescriptions for the First Layer pertain to both Frontages.
- c. Building heights shall conform to Table 8 and Table 14.
- d. Stories may not exceed 14-feet in height from finished floor to finished floor, except for a first floor Commercial Function, which shall be a minimum of 11-feet and may be a maximum of 25-feet. A single floor level exceeding 14-feet, or 25-feet at ground level, shall be counted as 2 Stories. Mezzanines extending beyond 33% of the floor area shall be counted as an additional floor.
- e. In a Parking Structure or garage, each above-ground level counts as a single Story regardless of its relationship to habitable Stories.
- f. Height limits do not apply to Attics or raised basements, masts, belfries, clock towers, chimney flues, water tanks, or elevator bulkheads. Attics shall not exceed 14-feet in height.

5.7.7 SPECIFIC TO ZONES OT-5H, OT-5C AND SPECIAL DISTRICT SD-A

- a. Awnings and Galleries may fully Encroach the Sidewalk to the Curb but must clear the Sidewalk vertically by at least 8-feet.
- b. Stoops, Lightwells, balconies, bay windows, and terraces may Encroach the First Layer 100% of its depth. Balconies and bay windows may Encroach the Sidewalk 25% of its depth. (Table 17d)
- c. Loading docks and service areas may be permitted on B-Grid Frontages only. Loading docks and service areas may only be permitted on A-Grid Frontages by Warrant.
- d. In the absence of a building Facade along any part of a Frontage Line, a Streetscreen shall be built coplanar with the Facade.
- e. Streetscreens should be between 3.5 and 8-feet in height. The Streetscreen may be replaced by a hedge or fence by approval of the DRC. Streetscreens shall have openings no larger than necessary to allow automobile and pedestrian access.
- f. A first level Residential or Lodging Function shall be raised a minimum of 18-inches from average Sidewalk grade.

5.8 BUILDING FUNCTION

- 5.8.1 GENERAL TO ZONES T2, T3, T4, T5
 - a. Buildings in each Transect Zone shall conform to the Functions on Table 10, Table 12 and Table 14. Functions that do not conform shall require approval by Warrant or Variance as specified on Table 12.

5.8.2 SPECIFIC TO ZONES T2, T3

- a. Accessory Functions of Restricted Office shall be permitted within an Outbuilding. See Table 10.
- 5.8.3 SPECIFIC TO ZONES T4, T5
 - a. Accessory Functions of Limited Lodging or Limited Office shall be permitted within an Outbuilding. See Table 10.
- 5.8.4 SPECIFIC TO ZONE T5
 - a. First Story Commercial Functions shall be permitted.
 - b. Manufacturing Functions within the first Story may be permitted by Variance.
- 5.8.5 SPECIFIC TO ZONE OT-3
 - a. The number of dwellings on each Lot is restricted to one within a Principal Building and one within an Accessory Building.
 - b. The building area available for a Home Occupation Office use on each Lot is restricted to the first Story of the Principal or Accessory Building.
- 5.8.6 SPECIFIC TO ZONES OT-3, OT-4R AND OT-4T
 - a. Habitable area of the Accessory Unit shall not exceed 600-square feet, excluding the parking area.

5.9 PARKING AND DENSITY CALCULATIONS

- 5.9.1 SPECIFIC TO ZONES T2, T3
 - a. Buildable Density on a Lot shall be determined by the actual parking provided within the Lot as applied to the Functions permitted in Table 10 and Table 11.
- 5.9.2 SPECIFIC TO ZONES T4, T5
 - a. Buildable Density on a Lot shall be determined by the sum of the actual parking calculated as that provided (1) within the Lot (2) along the parking lane corresponding to the Lot Frontage, and (3) by purchase or lease from a Civic Parking Reserve within the Pedestrian Shed, if available.
 - b. The actual parking may be adjusted upward according to the Shared Parking Factor of Table 11 to determine the Effective Parking. The Shared Parking Factor is available for any two Functions within any pair of adjacent Blocks.
 - c. Based on the Effective Parking available, the Density of the projected Function may be determined according to Table 10.
 - d. Within the overlay area of a Transit Oriented Development (TOD) the Effective Parking may be further adjusted upward by 30%.
 - e. The total Density within each Transect Zone shall not exceed that specified by an approved Regulating Plan based on Article 3 or Article 4.
 - f. Accessory Units do not count toward Density calculations.
 - g. Liner Buildings less than 30-feet deep and no more than two Stories shall be exempt from parking requirements.
- 5.9.3 SPECIFIC TO ZONES OT-3, OT-4R, OT-5H, OT-5C AND SPECIAL DISTRICT SD-A
 - a. The buildable Density on a Lot shall be governed by the height, Setback, and Lot coverage requirements only.

5.10 PARKING LOCATION STANDARDS

- 5.10.1 GENERAL TO ZONES T2, T3, T4, T5, OT-3, OT-4R, OT-4T AND OT-5H
 - a. Parking shall be accessed by Rear Alleys or Rear Lanes, when such are available on the Regulating
 - b. Open parking areas shall be masked from the Frontage by a Building or Streetscreen.
 - c. For buildings on B-Grids, open parking areas may be allowed unmasked on the Frontage by Warrant, except for corner Lots at intersections with the A-Grid.
- 5.10.2 GENERAL TO ZONES T2 AND T3
 - a. Open parking areas shall be located at the Second and Third Lot Layers, except that Driveways, drop-

SC26 Revised June 2014

- offs and unpaved parking areas may be located at the First Lot Layer. (Table 17d)
- b. Garages shall be located at the Third Lot Layer except that side or rear entry types may be allowed in the First or Second Layer by Warrant.
- 5.10.3 SPECIFIC TO ZONES T3, T4, OT-3, OT-4R AND OT-4T
 - a. Driveways at Frontages shall be no wider than 10-feet in the First Layer.
- 5.10.4 SPECIFIC TO ZONES T4, OT-4R AND OT-4T
 - a. All parking areas and garages shall be located at the Second or Third Layer. (Table 17d)
- 5.10.5 SPECIFIC TO ZONE T5
 - a. All parking lots, garages, and Parking Structures shall be located at the Second or Third Lot Layer. (Table 17d)
 - b. Vehicular entrances to parking lots, garages, and Parking Structures shall be no wider than 24-feet at the Frontage.
 - c. Primary pedestrian exits from all parking lots, garages, and Parking Structures shall be directly to a Frontage Line (i.e., not directly into a building) except underground garage levels that may be exited by pedestrians directly into a building.
 - d. Parking Structures on the A-Grid shall have Liner Buildings lining the first and second Stories.
 - e. A minimum of one bicycle rack place shall be provided within the Public or Private Frontage for every ten vehicular parking spaces.
- 5.10.6 SPECIFIC TO ZONES OT-4R, OT-5H AND OT-5C
 - a. All parking lots, garages, and Parking Structures shall be located at the Second or Third Lot Layer. (Table 17d)
 - b. Vehicular entrances to parking lots, garages, and Parking Structures shall be no wider than 24-feet at the Frontage.
 - c. Primary pedestrian exits from all parking lots, garages, and Parking Structures shall be directly to a Frontage Line (i.e., not directly into a building) except underground garage levels that may be exited by pedestrians directly into a building. Secondary exits may be provided from the building to a parking lot or garage or Parking Structure.
 - d. Parking Structures on the A-Grid shall have Liner Buildings lining the first and second Stories.
 - e. A minimum of one bicycle rack place shall be provided within the Public or Private Frontage for every ten vehicular parking spaces.
 - f. All parking lots and Parking Structures shall be provided Driveway access from B-Grid Streets only.
- 5.10.7 SPECIFIC TO ZONES OT-3, OT-4R, OT-4T, OT-5H, OT-5C AND SPECIAL DISTRICT SD-A
 - a. All parking shall be located where indicated in the specific Frontage standards in Table 15D through I.
 - b. Any parking provided shall meet the city's standards for parking lot design as established in the UDC.
- 5.11 LANDSCAPE STANDARDS
- 5.11.1 GENERAL TO ZONES T2, T3, T4, T5, OT-3, OT-4R, OT-4T, OT-5H, OT-5C AND SPECIAL DISTRICT SD-A
 - a. Trees and shrubs shall be planted in accordance with the Landscaping Requirements of Section 10.407 of the Unified Development Code, except where in conflict with the SmartCode.
- 5.11.2 SPECIFIC TO ZONES T2, T3, T4, OT-3, OT-4R AND OT-4T
 - a. The First Layer may not be paved, with the exception of Driveways and walkways. (Table 17d)
- 5.11.3 SPECIFIC TO ZONES T3 AND OT-3
 - a. A minimum of two trees shall be planted within the First Layer for each 30-feet of Frontage Line or portion thereof. (Table 17d)
 - b. Trees may be of single or multiple native species.
 - c. Trees shall be naturalistically clustered.
 - d. Lawn shall be permitted by Right.
- 5.11.4 SPECIFIC TO ZONES T4, OT-4R AND OT-4T

- a. A minimum of one tree shall be planted within the First Layer for each 30-feet of Frontage Line or portion thereof. (Table 17d)
- b. Trees shall be a single native species and may match the species of street trees on the Public Frontage.
- c. Lawn shall be permitted By Right.
- 5.11.5 SPECIFIC TO ZONES T5, OT-4R AND OT-5H AND OT-5C
 - a. Trees shall not be required in the First Layer where prevented by the Private Frontage.
 - b. The First Layer may be paved to match the pavement of the Public Frontage.
- 5.12 SIGNAGE STANDARDS
- 5.12.1 GENERAL TO ZONES T2, T3, T4, T5, OT-3 AND OT-4R
 - a. There shall be no signage permitted additional to that specified in this section.
 - b. The address number, no more than 6-inches measured vertically, shall be attached to the building in proximity to the Principal Entrance or at a mailbox.
- 5.12.2 SPECIFIC TO ZONES T2 AND T3
 - a. Signage shall not be illuminated.
- 5.12.3 SPECIFIC TO ZONES T4 AND T5
 - a. Signage shall be externally illuminated, except that signage within the Shopfront glazing may be neon lit.
- 5.12.4 SPECIFIC TO ZONES T2, T3 AND T4
 - a. One blade sign for each business may be permanently installed perpendicular to the Facade within the First Layer. Such a sign shall not exceed a total of 4-square feet and shall clear 8-feet above the Sidewalk.
- 5.12.5 SPECIFIC TO ZONE T5
 - a. Blade signs, not to exceed 6-square feet for each separate business entrance, may be attached to and should be perpendicular to the Facade, and shall clear 8-feet above the Sidewalk.
 - b. A single external permanent sign band may be applied to the Facade of each building, providing that such sign not exceed 3-feet in height by any length.
- 5.12.6 SPECIFIC TO ALL OT ZONES
 - a. All new signage in Old Town shall comply with Sections 10.410.4, 10.410.5, 10.410.6, 10.410.8, 10.410.9, 10.410.10 of the UDC, as well as with the following Downtown Sign District standards.
- 5.12.7 NON-CONFORMING STRUCTURES AND SIGNS IN OLD TOWN SPECIFIC TO OT ZONES
 - a. The requirement and standards of this section shall apply to signs for all non-Residential uses and Home Occupations within the boundaries of the Historic Overlay District, as defined in the UDC.
 - b. The provisions contained in this section are intended to encourage high standards for signs within the Historic District, so they should be appropriate for Old Town Hutto and add to the aesthetic appearance and attractiveness. Signs within the Historic District should:
 - i. adequately and effectively communicate business identity and type to the public:
 - ii. be pedestrian oriented and as small in size and few in number as consistent with their purpose of communicating identification and essential information;
 - iii. protect the Historic District from sign clutter and visual blight resulting from excessive and redundant signs;
 - iv. be architecturally compatible with the style, composition, materials, colors and details of the building and its vicinity and contribute to the historic character of the Historic District.
 - v. Unless otherwise specifically stated below all provisions of the Heart of Hutto Old Town Master Plan and/or City of Hutto UDC shall apply to the District as appropriate.
- 5.12.8 PRIMARY AND SECONDARY SIZE CALCULATION SPECIFIC TO OT ZONES
 - a. Single-tenant facades 30-feet in length and under shall be allowed one and one-half (1½) square feet of sign area per one horizontal linear feet of facade.

SC28 Revised June 2014

- b. Multi-tenant facades 30-feet in length and under shall be allowed 2-square feet of sign area per one horizontal linear feet of facade.
- c. Facades over 30-feet in length shall be allowed 1-square feet of sign area per one horizontal linear feet of facade.
- d. All square footage is calculated based on the width of the building facade on which the sign is to be placed and are subject to the maximum sizes described in the following sections of this ordinance.

5.12.9 PRIMARY SIGNS - SPECIFIC TO OT ZONES

- a. Canopy Sign. Shall not exceed 16-square feet in area.
- b. Projection Sign. Shall not exceed 12-square feet in area. The top of all projecting signs shall be located below the roofline and at a height not greater that 16-feet above the ground. The base of all projecting signs shall be no less than 8-feet above the ground. Projecting signs shall not project from the exterior wall of the building more than 6-feet.
- c. Low Profile Sign. Allowed only on developed Commercial property in all OT Transect Zones except OT-3. Properties with less than 75-feet of Street Frontage may not have Low Profile Signs that exceed 40-square feet in area. Properties with inadequate building Setbacks are prohibited from using Low Profile Signs.
- d. Wall Sign. Shall not exceed the maximum allowable square footage for Primary Sign as determined by calculation from Section 10.410 of the UDC. In cases where allowable square footage is calculated to be greater than 100-square feet, the maximum size of the Wall Sign will be 100-square feet.
- e. Secondary Sign Awning Sign. Shall not exceed 16-square feet in area. No Awning Sign shall extend above the top of the Awning.
- f. Hanging Sign. Shall not exceed 8-square feet in area, and provide a minimum of 6-feet of clearance between the Sidewalk surface and the bottom of the sign. Sign shall be within 6-feet of the door. Sign must hang perpendicular to the Facade of the building.

5.12.10 ACCESSORY SIGNS - SPECIFIC TO OT ZONES

- a. Alley Signs. Shall not exceed 16-square feet in area. Building Frontage along publicly accessed right-of-way alleys may be designated as Facade by property owners provided there is at least one access point to the business being advertised through the alley. In such cases, Alley Signs shall be designated Primary Signs and subject to applicable Primary Sign regulations.
- b. Mural Sign. Covers all or substantially all of wall. Must have design content approval from the Planning and Zoning Commission. The HPC may, when requested, provide guidance to city staff and applicants with regard to historic context. Commercial advertisements shall not constitute more than 25% of total Mural area.
- c. Window Sign. The coverage area shall not exceed 30% of the window area.

5.12.11 OTHER PROVISIONS - SPECIFIC TO OT ZONES

- a. Architectural Features. No sign in the downtown sign district can cover or otherwise obstruct any distinctive Architectural Features of the building, and all signs must comply with the Architectural Design Standards as outlined in the Heart of Hutto Old Town Master Plan. The HPC may, when requested, provide guidance to city staff and applicants with regard to sign placement. Mechanical equipment shall not be mounted on Awnings where it is visible from the public Street.
- b. Internally illuminated sign. Internally illuminated signs are not allowed in Old Town Hutto. Sign lighting must be either external or halo-type.
- c. Pole/pylon Sign. Pole or pylon Signs are not allowed in Old Town Hutto.

5.13 ARCHITECTURAL STANDARDS

5.13.1 GENERAL TO ZONES T3, T4 AND T5

- a. Building wall materials may be combined on each Facade only horizontally, with the heavier below the lighter.
- b. Streetscreens should be constructed of a material matching the adjacent building Facade.
- c. All openings, including porches, Galleries, Arcades and windows, with the exception of Shopfronts, shall be square or vertical in proportion.
- d. Openings above the first Story shall not exceed 50% of the total building wall area, with each Facade being calculated independently.
- e. Doors and windows that operate as sliders are prohibited along Frontages.
- f. Pitched roofs, if provided, shall be symmetrically sloped no less than 5:12, except that roofs for porches and attached sheds may be no less than 2:12.
- g. The exterior finish material on all Facades shall be limited to brick, stone, wood siding, cementitious siding, and/or stucco.
- h. Flat roofs shall be enclosed by parapets a minimum of 42-inches high, or as required to conceal mechanical equipment to the satisfaction of the DRC.
- i. Balconies and porches shall be made of painted wood or metal.

5.13.2 SPECIFIC TO ZONES OT-3, OT-4R, OT-4T, OT-5H, OT-5C AND SPECIAL DISTRICT SD-A

- a. All new development and redevelopment shall meet the standards established in Appendix A Old Town Architectural Design Standards.
- b. Any new and reconstructed buildings that do not comply with this appendix shall only be approved if a Warrant is granted by the HPC after a recommendation from the DRC. In reviewing the Warrant application the HPC shall grant the Warrant based on the extent to which standards in the Appendix can be feasibly met and the extent to which the proposed changes meet the Intent of the Old Town Master Plan.

SC30 Revised June 2014

SMARTCODE

Hutto, Texas

Table 1: Transect Zone Descriptions. This tables provides descriptions of the character of each T-zone.

T1

T-1 NATURAL

T-1 Natural Zone consists of lands approximating or reverting to a wilderness condition, including lands unsuitable for settlement due to topography, hydrology or vegetation.

General Character: Natural landscape with some agricultural use

Building Placement: Not applicable
Frontage Types: Not applicable
Typical Building Height: Not applicable
Type of Civic Space: Parks, Greenways



T-2 RURAL

T-2 Rural Zone consists of sparsely settled lands in open or cultivated states. These include woodland, agricultural land, and grassland. Typical buildings are farmhouses, agricultural buildings, cabins, and villas.

General Character: Primarily agricultural with woodland & wetland and scattered

buildings

Building Placement: Variable Setbacks
Frontage Types: Not applicable
Typical Building Height: 1- to 2-Story
Type of Civic Space: Parks, Greenways



T-3 SUB-URBAN

T-3 Sub-Urban Zone consists of low Density Residential areas, adjacent to higher zones that have some mixed use. Home Occupations and Outbuildings are allowed. Planting is naturalistic and Setbacks are relatively deep. Blocks may be large and the Roads irregular to accommodate natural conditions.

General Character: Lawns and landscaped yards surrounding detached single-

family Houses; pedesttrians occasionally

Building Placement: Large and variable front and side yard Setbacks
Frontage Types: Porches, fences, naturalistic tree planting

Typical Building Height: 1- to 2-Story with some 3-Story

Type of Civic Space: Parks, Greenways



T-4 GENERAL URBAN

T-4 General Urban Zone consists of a Mixed-Use but primarily Residential urban fabric. It may have a wide range of building types: single, Sideyard, and Rowhouses. Setbacks and landscaping are variable. Streets with curbs and Sidewalks define medium-sized Blocks.

General Character: Mix of Houses, Townhomes and small Apartment buildings

with scattered Commercial activity; balance between landscape and buildings; presence of pedestrians

Building Placement: Shallow to medium front and side yard Setbacks

Frontage Types: Porches, fences, Dooryards

Typical Building Height: 2- to 3-Story
Type of Civic Space: Squares, Greens



T-5 URBAN CENTER

T-5 Urban Center Zone consists of higher density Mixed-Use building that accommodate Retail, Offices, Rowhouses and Apartments. It has a tight network of Streets, with wide Sidewalks, steady Street tree planting and buildings set close to the Sidewalks.

General Character: Shops mixed with Townhouses, larger Apartment houses,

Offices, workplace and Civic Buildings; predominantly attached buildings; trees within the public right-of-way;

substantial pedestrian activity


Building Placement: Shallow Setbacks or none; buildings oriented to Street

defining a Street wall

Frontage Types: Stoops, Shopfronts, Galleries

Typical Building Height: 2- to 5-Story with some variation

Type of Civic Space: Parks, Plazas, and Squares, median landscaping



T-6 URBAN CORE

T-6 Urban Core Zone consists of the highest density and height, with the greatest variety of uses, and Civic Buildings of regional importance. It may have larger Blocks; Streets have steady Street tree planting and buildings are set close to wide Sidewalks. Typically only large towns and cities have an Urban Core Zone.

General Character: Medium to high-Density Mixed-Use buildings, entertainment,

Civic and cultural uses. Attached buildings forming a continuous Street wall; trees within the public right-of-way;

highest pedestrian and transit activity

Building Placement: Shallow Setbacks or none; buildings oriented toward the

Street, defining a Street wall

Frontage Types: Stoops, Dooryards, Forecourts, Shopfronts, Galleries

Typical Building Height: 4-plus Story with a few shorter buildings

Type of Civic Space: Parks, Plazas and Squares; median landscaping

Table 1A: Old Town Transect Zone Descriptions. This tables provides descriptions of the character of each Old Town T-zone.



OT-3 TRADITIONAL NEIGHBORHOOD

OT-3 Residential Zone consists of traditional residential neighborhood areas adjacent to the downtown core. Home Occupations and Outbuildings are allowed. Planting is naturalistic and Setbacks are relatively deep. Blocks may be large and the Roads irregular to accommodate natural conditions.

General Character: Lawns, and landscaped yards surrounding detached single-family

Houses; pedestrians occasionally

Building Placement: Large and variable front and side yard Setbacks
Frontage Types: Porches, fences, naturalistic tree planting

Typical Building Height: 1- to 2-Story

Type of Civic Space: Parks, Greenways

OT-4R

OT-4R URBAN RESIDENTIAL

OT-4R Urban Residential Zone consists of Mixed Use but primarily Residential urban fabric. It may have a wide range of building types: single, Sideyard, and Rowhouses. Setbacks and landscaping are variable. Streets with Curbs and Sidewalks define medium-sized Blocks.

General Character: Mix of Houses, Townhouses & small Apartment buildings, with corner Commercial activity; balance between landscape and

buildings; presence of pedestrians

Building Placement: Shallow to medium front and side yard Setbacks

Frontage Types: Porches, fences, Dooryards

Typical Building Height: 2- to 3-Story
Type of Civic Space: Squares, Greens



OT-4T TRANSITION

OT-4T Transition Zone consists of a Mixed Use neighborhood that provides a transition to the adjoining Residential neighborhood. Buildings are generally Residential that may accommodate Retail, Offices and personal services.

General Character: Mix of businesses (Retail, Office, and Lodging) located in Residential

structures: single-family, Townhomes, Live-Work; presence of

pedestrians

Building Placement: Shallow to medium front and side yard Setbacks

Frontage Types: Porches, fences, Dooryards

Typical Building Height: 1- to 2-Story
Type of Civic Space: Squares, Greens



OT-5H HISTORIC

OT-5H Historic Zone consists of Hutto's downtown core which is a high intensity Mixed Use neighborhood with buildings that accommodate Retail, Offices, Live-Work and Apartments. It has a tight network of Streets, with wide Sidewalks, steady street tree planting and buildings set close to the Sidewalks.

General Character: Historic and new buildings; shops mixed with restaurants, Offices,

workplace, Civic Buildings, Live-Work, and Apartments;

predominantly attached buildings; trees within the public right-of-way;


substantial pedestrian activity

Building Placement: Shallow Setbacks or none; buildings oriented to Street defining a

Street wall

Frontage Types: Stoops, Shopfronts, Galleries

Typical Building Height: 1- to 2-Story
Type of Civic Space: Plazas, Squares



OT-5C CO-OP SITE

OT-5C Co-Op Zone consists of the highest Density and height, with the greatest variety of uses, and Civic Buildings of local importance. It has a tight network of Streets that have steady street tree planting and buildings are set close to wide Sidewalks. General Character: Shops mixed with restaurants, larger Apartment houses, Offices,

workplace, Civic and cultural uses; attached buildings forming a continuous Street wall; trees within the public right-of-way; high level


of pedestrian activity

Building Placement: Shallow Setbacks or none; buildings oriented to Street defining a

Street wall

Frontage Types: Stoops, Shopfronts, Galleries
Typical Building Height: 3- to 5-Story with some variation

Type of Civic Space: Parks, Plazas, and Squares, median landscaping



SD-A ARTERIAL

SD-A Arterial Special District Zone consists of lower intensity Commercial (Retail, Office, light industrial) located in low Density auto-oriented buildings; some parking permitted along the public right-of-way; limited pedestrian activity

General Character: Mix of businesses (Retail, Office, light industrial) located in low

Density auto-oriented buildings; some parking permitted along the $\,$

public right-of-way; limited pedestrian activity

Building Placement: Medium to deep Setbacks; surface parking along the Street

Frontage Types: Sub-urban Commercial

Typical Building Height: 1- to 2-Story

Type of Civic Space: Parks, Greens; median landscaping

SC32 Revised June 2014

Table 3A: Vehicular Lane Dimensions. These tables assign lane widths to Transect Zones. The Design ADT (Average Daily Traffic) is the determinant for each of these sections. Specific requirements for truck and transit bus routes and truck loading shall be decided by Warrant.

DESIGN SPEED	TRAVEL LANE WIDTH	T1	T2	T3	T4	T5	<u>.</u>	
Below 20 mph	8 feet		•	•			•	BY RIGHT
20-25 mph	9 feet		•	•	•			BY WARRANT
25-35 mph	10 feet		•	•	•	•]	
25-35 mph	11 feet	•	•			•]	
Above 35 mph	12 feet	•	-			•]	
DESIGN SPEED	PARKING LANE WIDTH							
20-25 mph	(Angle) 18 feet					•]	
20-25 mph	(Parallel) 6 feet			•	•]	
20-25 mph	(Parallel) 7 feet				•	•]	
25-35 mph	(Parallel) 8 feet			•	•	•]	
Above 35 mph	(Parallel) 9 feet					•]	
DESIGN SPEED	EFFECTIVE TURNING RADIUS				(Se	ee Table 17b)	_	
Below 20 mph	5-10 feet			•	•	•]	
20-25 mph	10-15 feet	•	-	•	-	-]	
25-35 mph	15-20 feet	•	-	-	•	•]	
DESIGN SPEED	TRAVEL LANE WIDTH	OT-3	OT-4R	OT-4T	OT-5H	OT-5C	SD-A	
Below 20 mph	8 feet	•]
20-25 mph	9 feet		•	•	•	•]
25-35 mph	10 feet		-		-	-		1
25-35 mph	11 feet						•]
Above 35 mph	12 feet						•]
DESIGN SPEED	PARKING LANE WIDTH							_
20-25 mph	(Angle) 18 feet			•	•	•		

DESIGN SPEED	EFFECTIVE TURNING RADIUS					(See	Table 17b)
Below 20 mph	5-10 feet	•	•	•	•	•	
20-25 mph	10-15 feet	•		•		•	
25-35 mph	15-20 feet	•		•		•	•

(Angle) 18 feet (Parallel) 6 feet

(Parallel) 7 feet


(Parallel) 8 feet (Parallel) 9 feet

20-25 mph 20-25 mph

25-35 mph

Above 35 mph


TABLE 4A: Public Frontages General: The Public Frontage is the area between the private Lot Line and the edge of the vehicular lanes. Dimensions are given in Table 4B.



Revised June 2014


TABLE 4B: Public Frontages - Specific. This table assembles prescriptions and dimensions for the Public Frontage elements - Curbs, walkways and Planters - relative to specific Thoroughfare types within Transect Zones. Table 4B-a assembles all of the elements for the various street types. Locally appropriate planting species should be filled in to the calibrated Code. OT-4 includes OT-4R and OT-5 includes OT-5H and OT-5C.


T1 T2 T3 T3 T4 OT-3 T5 SD-A T5 SD-A TRANSECT ZONE T1 T2 T3 OT-3 T4 T5 OT-5 SD-A OT-4 OT-4 OT-5 OT-4 OT-5 CS-DR-AV-BV HW & RD RD & ST ST-DR-AV ST-DR-AV-BV CS-DR-AV-BV **Public Frontage Type** a. Assembly: The principal variables are the type and dimension of Curbs, walkways, Planters and landscape. 16-24 feet 12-24 feet 12-18 feet 12-18 feet 18-24 feet 18-30 feet Total Width b. Curb. The detailing of the edge of the vehicular pavement, incorporating drainage. Open Swale Open Swale Raised Curb Raised Curb Raised Curb Raised Curb Type 10-30 feet 10-30 feet 5-20 feet Radius 5-20 feet 5-20 feet 5-20 feet c. Walkway. The pavement dedicated exclusively to pedestrian activity. Type Path Optional Path Sidewalk Sidewalk Sidewalk Sidewalk 4-8 feet 4-8 feet 4-8 feet 12-20 feet 12-30 feet n/a d. Planter: The layer which accommodates street trees and other landscape. Clustered Clustered Regular Regular Regular Opportunistic Arrangement Species Multiple Multiple Alternating Single Single Single Planter Type Continuous Swale Continuous Swale Continuous Planter Continuous Planter Continuous Planter Tree Well Planter Width 8 feet - 16 feet 8 feet - 16 feet 8 feet - 12 feet 4 feet - 6 feet 4 feet - 6 feet 8 feet - 12 feet e. Landscape. The recommended plant species. (See Table 6) f. Lighting. The recommended public lighting.



THOROUGHFARE TYPES

Highway	HW
Boulevard	BV
Avenue	AV
Commercial Street	CS
Drive	DR
Park Street	PS
Street	ST
Road	RD
Rear Alley	RA
Rear Lane	RL
Bicycle Trail	ВТ
Bicycle Lane	BL
Bicycle Route	BR
Shared Use Path	PA
Transit Route	TR






Thoroughfare Type
Transect Zone Assignment
Right-of-Way Width
Pavement Width
Movement
Design Speed
Pedestrian Crossing Time
Traffic Lanes
Parking Lanes
Curb Radius
Walkway Type
Planter Type
Curb type
Landscape Type
Transportation Provision

PA-16-10
Shared Use Path
T1, T2, T3, OT-3, OT-4T, OT-4R
16'
10'
Yield
15 mph
N/A
1 shared
0
N/A
paved asphalt
none
Swale
none
BR/PA


RL-30-12
Rear Lane
T3, T4, OT-3, OT-4R, OT-4T
30'
12'
Yield
5 mph
3 seconds
1 shared
0
special
none
none
Swale
none
BR


SC36 Revised June 2014



THOROUGHFARE TYPES

Highway	HW
Boulevard	BV
Avenue	ΑV
Commercial Street	CS
Drive	DR
Park Street	PS
Street	ST
Road	RD
Rear Alley	RA
Rear Lane	RL
Bicycle Trail	ВТ
Bicycle Lane	BL
Bicycle Route	BR
Shared Use Path	PA
Transit Route	TR






Thoroughfare Type
Transect Zone Assignment
Right-of-Way Width
Pavement Width
Movement
Design Speed
Pedestrian Crossing Time
Traffic Lanes
Parking Lanes
Curb Radius
Walkway Type
Planter Type
Curb type
Landscape Type

Transportation Provision


RA-24-24
Rear Alley
T4, T5, OT-4R, OT-5 (all subzones)
24'
24'
Yield
5 mph
6 seconds
1 shared
0
special
none
none
none
none
BR
· · · · · · · · · · · · · · · · · · ·


RD-50-24
Road
T1, T2
50'
24'
free
35 mph
6 seconds
2
0
20'
Path optional
opportunistic
Swale
clustered
BR
-



THOROUGHFARE TYPES

Highway	HW
Boulevard	BV
Avenue	ΑV
Commercial Street	CS
Drive	DR
Park Street	PS
Street	ST
Road	RD
Rear Alley	RA
Rear Lane	RL
Bicycle Trail	ВТ
Bicycle Lane	BL
Bicycle Route	BR
Shared Use Path	PA
Transit Route	TR






Thoroughfare Type
Transect Zone Assignment
Right-of-Way Width
Pavement Width
Movement
Design Speed
Pedestrian Crossing Time
Traffic Lanes
Parking Lanes
Curb Radius
Walkway Type
Planter Type
Curb type
Landscape Type
Transportation Provision

KD-00-24
Road
T1, T2
60'
24'
free
45 mph
6 seconds
2
0
25'
8' shared use Path
opportunistic
Swale
clustered
BR


DR-44-24
Drive
T3, T4, OT-3, OT-4T
44'
24'
slow
20 mph
6 seconds
2
1
10'
5' sidewalk
5' continuous Planter
vertical
trees 30' o.c.
BR


SC38 Revised June 2014



THOROUGHFARE TYPES

Highway	HW
Boulevard	BV
Avenue	AV
Commercial Street	CS
Drive	DR
Park Street	PS
Street	ST
Road	RD
Rear Alley	RA
Rear Lane	RL
Bicycle Trail	ВТ
Bicycle Lane	BL
Bicycle Route	BR
Shared Use Path	PA
Transit Route	TR






Thoroughfare Type
Transect Zone Assignment
Right-of-Way Width
Pavement Width
Movement
Design Speed
Pedestrian Crossing Time
Traffic Lanes
Parking Lanes
Curb Radius
Walkway Type
Planter Type
Curb type
Landscape Type
Transportation Provision


PS-80-40
Park Street
T4, T5
80'
40'
slow
20 mph
5 seconds per side
2
2
10'
12' Sidewalk
tree wells
vertical
trees 30' o.c.
BR


ST-44-24
Street
T3, OT-3, OT-4T, OT-4R
44'
24'
slow
20 mph
6 seconds
2
1
10'
5' Sidewalk
5' continuous Planter
vertical
trees 30' o.c.
BR



THOROUGHFARE TYPES

Highway	HW
Boulevard	BV
Avenue	ΑV
Commercial Street	CS
Drive	DR
Park Street	PS
Street	ST
Road	RD
Rear Alley	RA
Rear Lane	RL
Bicycle Trail	ВТ
Bicycle Lane	BL
Bicycle Route	BR
Shared Use Path	PA
Transit Route	TR






Thoroughfare Type
Transect Zone Assignment
Right-of-Way Width
Pavement Width
Movement
Design Speed
Pedestrian Crossing Time
Traffic Lanes
Parking Lanes
Curb Radius
Walkway Type
Planter Type
Curb type
Landscape Type
Transportation Provision

31-30-32
Street
T3, T4, OT-3, OT-4T
50'
32'
slow
20 mph
8 seconds
2
2
10'
5' Sidewalk
4' continuous Planter
vertical
trees 30' o.c.
BR


ST-50-28
Street
T4
50'
28'
free
25 mph
7 seconds
2
1
10'
5' Sidewalk
6' continuous Planter
vertical
trees 30' o.c.
BR


SC40 Revised June 2014



THOROUGHFARE TYPES

Highway	HW
Boulevard	BV
Avenue	AV
Commercial Street	CS
Drive	DR
Park Street	PS
Street	ST
Road	RD
Rear Alley	RA
Rear Lane	RL
Bicycle Trail	ВТ
Bicycle Lane	BL
Bicycle Route	BR
Shared Use Path	PA
Transit Route	TR






Thoroughfare Type
Transect Zone Assignment
Right-of-Way Width
Pavement Width
Movement
Design Speed
Pedestrian Crossing Time
Traffic Lanes
Parking Lanes
Curb Radius
Walkway Type
Planter Type
Curb type
Landscape Type
Transportation Provision


S1-5U-28-Y
Street
T3, OT-3, OT-4T
50'
28'
Yield
15 mph
7 seconds
2 shared
2 boxed
10'
5' Sidewalk
6' continuious Planter
vertical
trees 30' o.c.
BR


ST-50-34
Street
T4, T5
50'
34'
slow
25 mph
8 seconds
2
2
10'
8' Sidewalk
tree wells
vertical
trees 30' o.c.
BR



THOROUGHFARE TYPES

monocom /mc mile	
Highway	HW
Boulevard	BV
Avenue	AV
Commercial Street	CS
Drive	DR
Park Street	PS
Street	ST
Road	RD
Rear Alley	RA
Rear Lane	RL
Bicycle Trail	ВТ
Bicycle Lane	BL
Bicycle Route	BR
Shared Use Path	PA
Transit Route	TR
	Boulevard Avenue Commercial Street Drive Park Street Street Road Rear Alley Rear Lane Bicycle Trail Bicycle Lane Bicycle Route Shared Use Path






Thoroughfare Type
Transect Zone Assignment
Right-of-Way Width
Pavement Width
Movement
Design Speed
Pedestrian Crossing Time
Traffic Lanes
Parking Lanes
Curb Radius
Walkway Type
Planter Type
Curb type
Landscape Type
Transportation Provision

Commercial Street
T5, OT-5H, OT-5C, SD-A
80'
56'
slow
25 mph
14 seconds
2
2 angled @ 18' marked
10'
12' Sidewalk
tree wells
vertical
trees 30' o.c.
BR


CS-60-36							
Commercial Street							
T5							
60'							
36'							
slow							
25 mph							
9 seconds							
2							
both sides @ 7' marked							
10'							
12' Sidewalk							
tree wells							
vertical							
trees 30' o.c.							
BR							


SC42 Revised June 2014



THOROUGHFARE TYPES

monocom /mc mile	
Highway	HW
Boulevard	BV
Avenue	ΑV
Commercial Street	CS
Drive	DR
Park Street	PS
Street	ST
Road	RD
Rear Alley	RA
Rear Lane	RL
Bicycle Trail	ВТ
Bicycle Lane	BL
Bicycle Route	BR
Shared Use Path	PA
Transit Route	TR
	Boulevard Avenue Commercial Street Drive Park Street Street Road Rear Alley Rear Lane Bicycle Trail Bicycle Lane Bicycle Route Shared Use Path






Thoroughfare Type
Transect Zone Assignment
Right-of-Way Width
Pavement Width
Movement
Design Speed
Pedestrian Crossing Time
Traffic Lanes
Parking Lanes
Curb Radius
Walkway Type
Planter Type
Curb type
Landscape Type
Transportation Provision


Avenue
T5
90'
60'
slow
25 mph
18 seconds
2
2 angled @ 18' marked
10'
10' Sidewalk
tree wells
vertical
trees 30' o.c.
BR

AV-75-40							
Commercial Street							
T3, T4, OT-5 (all subzones), SD-A							
75'							
40'							
free							
30 mph							
13 seconds							
2							
2							
10'							
6' Sidewalk							
7' continuous Planter							
vertical							
trees 30' o.c.							
BR							



THOROUGHFARE TYPES

INUKUUUNFAKE ITPES	
Highway	HW
Boulevard	BV
Avenue	AV
Commercial Street	CS
Drive	DR
Park Street	PS
Street	ST
Road	RD
Rear Alley	RA
Rear Lane	RL
Bicycle Trail	ВТ
Bicycle Lane	BL
Bicycle Route	BR
Shared Use Path	PA
Transit Route	TR



Thoroughfare Type Transect Zone Assignment
Transect Zone Assignment
Right-of-Way Width
Pavement Width
Movement
Design Speed
Pedestrian Crossing Time
Traffic Lanes
Parking Lanes
Curb Radius
Walkway Type
Planter Type
Curb type
Landscape Type
Transportation Provision

AV-90-56					
Avenue					
T3, T4, T5					
90'					
56'					
slow					
25 mph					
16 seconds					
4					
both sides @ 8' marked					
10'					
6' Sidewalk					
7' continuous Planter					
Curb or Swale					
trees 30' o.c.					
BR/TR					

SC44 Revised June 2014

TABLE 6: Public Planting. This table shows six common types of street tree shapes and their appropriateness within the Transect Zones. The local planning office selects species appropriate for the bioregion.

	T1	T2	T3 OT-3	T4 OT-4	T5 OT-5	SD-A	
Columnar	•	•	•	•	•		
Oval	•	•	•	•	•		
Ball	•	•	•	•	•		
Pyramid	•	•	•	•			
Umbrella	•	•	•	•			
Vase	•	•	•	•			

Note: The OT-4 zone includes OT-4R and OT-4T, OT-5 zone includes all the subzones: OT-5H and OT-5C.

TABLE 7: Private Frontages. The Private Frontage is the areas between the building Facades and the Lot lines.

TABLE 7. I Tivate Frontages. The Frivate Frontage is the	SECTION PLAN				
	LOT► ◀ R.O.W.	LOT► ◀ R.O.W.			
	PRIVATE ► ◀ PUBLIC	PRIVATE ► ◀ PUBLIC			
	FRONTAGE FRONTAGE	FRONTAGE FRONTAGE			
a. Common Yard: a planted Frontage wherein the Facade is set back substantially from the Frontage Line. The front yard created remains unfenced and is visually continuous with adjacent yards, supporting a common landscape. The deep Setback provides a buffer from the higher speed Thoroughfares.		T2 T3			
b. Porch & Fence: a planted Frontage where the Facade is set back from the Frontage Line with an attached porch		T3 OT-3			
permitted to Encroach. A fence at the Frontage Line maintains street spatial definition. Porches shall be no less than 8 feet deep.		T4 OT-4T			
c. Terrace or Lightwell: a frontage wherein the Facade is		T4 OT-4R			
I setback back from the Frontage Line by an elevated terrace or sunken Lightwell. This type buffers Residential use from		T5 OT-4T			
urban Sidewalks and removes the private yard from public encroachment. Terraces are suitable for conversion to		SD-A			
outdoor cafes. Syn: Dooryard.		J. J			
d. Forecourt: a Frontage wherein the Facade is close to the Frontage Line and the central portion is set back. The		T4 OT-4R			
forecourt created is suitable for vehicular drop-offs. This		T5 OT-4T			
type should be allocated in conjunction with other Frontage types. Large trees within the Forecourts may overhang the		SD-A OT-5H			
Sidewalks.		OT-5C			
e. Stoop: a Frontage wherein the Facade is aligned close to the Frontage Line with the first Story elevated from the		T4 OT-4R			
Sidewalk sufficiently to ensure privacy for the windows. The entrance is usually an exterior stair and landing. This type		T5 OT-4T			
is recommended for ground-floor Residential use.	i de la constante de la consta	SD-A OT-5H			
		OT-5C			
f. Shopfront: a Frontage wherein the Facade is aligned close to the Frontage Line with the building entrance at Sidewalk		T4 OT-4R			
grade. This type is conventional for Retail use. It has a substantial glazing on the Sidewalk level and an awning		T5 OT-5H			
that should overlap the Sidewalk to within 2 feet of the Curb. Syn: Retail Frontage.	Zi-William	OT-5C			
Cas. Of a rollings.		SD-A			
g. Gallery: a Frontage wherein the Facade is aligned close to the Frontage Line with an attached cantilevered shed or		T4 OT-4R			
lightweight colonnade overlapping the Sidewalk. This type		T5 OT-5H			
is conventional for Retail use. The Gallery shall be no less than 10 feet wide and should overlap the Sidewalk to within		OT-5C			
2 feet of the Curb.		SD-A			

SC46 Revised June 2014

TABLE 8: Building Configuration. This table shows the Configurations for different building heights for each Transect Zone. Recess Lines and Expression Lines shall occur on higher buildings as shown. Maximum height as specified in Tables 14k and 14A.k.




TABLE 9: Building Disposition. This table approximates the location of the structure relative to the boundaries of each individual Lot, establishing suitable basic building types for each Transect Zone.

a. Edgeyard: Specific Types - single-family House, Cottage, villa, Estate House, T2 urban villa. A building that occupies the center of its Lot with Setbacks on all sides. This is the least urban of types as the front yard sets it back from the T3 Frontage, while the side yards weaken the spatial definition of the public Thoroughfare space. The front yard is intended to be visually continuous with the T4 yards of adjacent buildings. The rear yard can be secured for privacy by fences OT-3 and a well placed Backbuilding and/or Outbuilding. OT-4R OT-4T SD-A b. Sideyard: Specific Types - Charleston single-House, double House, zero Lot T4 Line House, twin. A building that occupies one side of the Lot with the Setback to the other side. A shallow Frontage Setback defines a more urban condition. If the T5 adjacent building is similar with a blank side wall, the yard can be quite private. OT-4R This type permits systematic climatic orientation in response to the sun or the breeze. If a Sideyard House abuts a neighboring Sideyard House, the type is OT-4T known as a Twin or double House. Energy costs, and sometimes noise, are reduced by sharing a party wall in this Disposition. OT-50 SD-A c. Rearyard: Specific Types - Townhouse, Rowhouse, Live-Work unit, loft T4 building, Apartment House, Mixed Use Block, Flex Building, perimeter Block. A building that occupies the full Frontage, leaving the rear of the Lot as the sole **T5** yard. This is a very urban type as the continuous Facade steadily defines the public Thoroughfare. The rear Elevations may be articulated for functional OT-4T purposes. In its Residential form, this type is the Rowhouse. For its Commercial OT-5H form, the rear yard can accommodate substantial parking. OT-5C SD-A d. Courtyard: Specific Types - patio House. A building that occupies the T5 boundaries of its Lot while internally defining one or more private patios. This is the most urban of types, as it is able to shield the private realm from all sides OT-5C while strongly defining the public Thoroughfare. Because of its ability to accomodate incompatible activities, masking them from all sides, it is recommended for workshops, Lodging and schools. The high security provided by the continuous enclosure is useful for crime-prone areas. e. Suburban Arterial: A building that is Setback from the Street. Buildings that are SD-A P typically larger footprints accommodating light industrial and Commercial uses along arterial roadways or railroad corridors. Parking may be permitted along the Street frontage. Office parks may also be located along these corridors.

SC48 Revised June 2014

TABLE 10: Building Function. This table categorizes Building functions within Transect Zones. Parking requirements are corelated to functional intensity. For Specific Function and Use permitted By Right or by Warrant, see Tables 12 and 12A. Parking requirements do not apply to OT zones.

	T2 T3	T4	T5
a. RESIDENTIAL	Restricted Residential: The number of dwellings on each Lot is restricted to one within a Principal Building and one within an Accessory Building, with 2.0 parking places for each. Both dwellings shall be under single ownership. The habitable area of the Accessory Unit shall not exceed 440 sf, excluding the parking area.		Open Residential: The number of dwellings on each Lot is limited by the requirement of 1.0 parking places for each dwelling, a ratio which may be reduced according to the shared parking standards (See Table 11).
b. LODGING	requirement of 1.0 assigned parking place for each bedroom, up to five, in addition to the parking requirement for the dwelling. The Lodging must be owner occupied. Food service may be provided in	Limited Lodging: The number of bedrooms available on each Lot for lodging is limited by the requirement of 1.0 assigned parking place for each bedroom, up to twelve, in addition to the parking requirement for the dwelling. The Lodging must be owner occupied. Food service may be provided in the a.m. The maximum length of stay shall not exceed ten days.	Open Lodging: The number of bedrooms available on each Lot for lodging is limited by the requirement of 1.0 assigned parking place for each bedroom. Food service may be provided at all times. The area allocated for food service shal be calculated and provided with parking according to Retail Function.
c. OFFICE	Office use on each Lot is restricted to the first Story of the Principal or the Accessory Building and by the requirement of 4.0 assigned parking places per	Limited Office: The building area available for Office use on each Lot is limited to the first Story of the Principal Building and/or to the Accessory Building, and by the requirement of 4.0 assigned parking places per 1,000 square feet of net Office space in addition to the parking requirement for each dwelling.	Open Office: The building area available for Office use on each Lot is limited by the requirement of 3.0 assigned parking places per 1,000 square feet of net Office space.
d. RETAIL	at the first Story for each 300 dwelling units and by the requirement of 4.0 assigned parking places per	Limited Retail: The building area available for Retail use is limited to the first Story of buildings at corner locations, not more than one per Block, and by the requirement of 4.0 assigned parking places per 1,000 square feet of net Retail space in addition to the parking requirement of each dwelling. The specific use shall be further limited to neighborhood store or food service seating no more than 40.	
e. CIVIC	See Table 12	See Tables 12 & 12A	See Tables 12 & 12A
f. OTHER	See Table 12	See Tables 12 & 12A	See Tables 12 & 12A

Table 11: Parking Calculations. The sum of the required parking for any two functions listed on Table 11a below, when divided by the appropriate Shared Parking Factor, produces the actual parking needed for each site. Conversely, the actual parking may be multiplied by the Shared Parking Factor to determine the Effective Parking credit that controls the possible Densities. Parking requirements do not apply to OT Zones.

TABLE 11A. REQUIRED PARKING (See Table 10)

TABLE THE RECORDED FARRING (OCC TABLE TO)							
	T2 T3	T4	T5				
RESIDENTIAL	2.0 / dwelling	1.5 / dwelling	1.0 / dwelling				
LODGING	1.0 / bedroom	1.0 / bedroom	1.0 / bedroom				
OFFICE & RETAIL	4.0 / 1,000 sq.ft.	4.0 / 1,000 sq.ft.	3.0 / 1,000 sq.ft.				
CIVIC	To be determined by V	To be determined by Warrant					
OTHER	To be determined by Warrant						
OTHER	To be determined by Warrant						

TARLE 11R SHAPED DARKING FACTOR

TABLE 11B. SHA	RED PAR	KING FACTOR
Function	with	Function
RESIDENTIAL	. /	RESIDENTIAL
LODGING	\mathcal{N}	LODGING
OFFICE	X_1	OFFICE
RETAIL 12	14 1 14	RETAIL
~	13 1 13	7
	1	

Religious Assembly

Hutto, Texas

TABLE 12: Specific Function & Use. This table expands the categories of Table 10 to delegate specific Functions and uses within Transect Zones.

a. RESIDENTIAL	12	13	14	T5	f. OTHER: AGRICULTURE		12	T 3	T4	I
Mixed Use Block					Grain Storage					
Flex Building					Livestock Pen					
Apartment Building			-		Greenhouse					
Live/Work Unit		•	-	-	Stable					
Row House					Kennel					
Duplex House			•		g. OTHER: AUTOMOTIVE					
Courtyard House					Gasoline					
Sideyard House			•		Automobile Service					
Cottage					Truck Maintenance					
House			•		Drive-Through Facility					
Accessory Unit	•		-		Rest Stop					
. LODGING					Roadside Stand					
Hotel (no room limit)				•	Billboard					
Inn (up to 12 rooms)			-	-	Shopping Center					
Bed & Breakfast (up to 5 rooms)		•	-		Shopping Mall					
School Dormitory			•		h. OTHER: CIVIL SUPPORT					
. OFFICE					Fire Station					
Office Building					Police Station				-	
Live/Work Unit		•	•	•	Cemetery					
. RETAIL	•				Funeral Home				•	
Open-Market Building		•			Hospital					
Retail Building			-	•	Medical Clinic					
Display Gallery					i. OTHER: EDUCATION				-	
Restaurant					College					
Kiosk					High School					
Push Cart					Trade School					
Liquor Selling Establishment					Elementary School				-	
Special Services					Other - Childcare Center					
Adult Entertainment					j. OTHER: INDUSTRIAL					
e. CIVIC					Heavy Industrial Facility					
Bus Shelter			•		Light Industrial Facility					
Convention Center					Truck Depot					
Conference Center					Laboratory Facility					
Exhibition Center					Water Supply Facility					
Fountain or Public Art	•	•			Sewer and Waste Facility					
Library					Electric Substation					
Live Theater					Wireless Transmitter					
Movie Theater					Cremation Facility					
Museum					Warehouse					
Outdoor Auditorium					Produce Storage					
Parking Structure					Mini-Storage					
Passenger Terminal										
Playground										
Sports Stadium						-	BY RI	GHT		
Surface Parking Lot							BY W	ARRAN	JT	


SC50 Revised June 2014

SMARTCODE


Hutto, Texas

TABLE 12A: Specific Function & Use. This table expands the categories of Table 10 to delegate specific Functions and uses within Old Town Transect Zones.

a. RESIDENTIAL	OT-3	OT-4R	OT-4T	OT-5H	OT-5C	SD-A	f. OTHER: AGRICULTURE	OT-3	OT-4R	OT-4T	OT-5H	OT-5C	SD-A
Mixed Use Block				•			Grain Storage						
Flex Building						•	Livestock Pen						
Apartment Building		•		•		•	Greenhouse						
1.5 AM d- 11-24							(Accessory Use only)						
Live/Work Unit		-			-	•	Stable						
Row House		-	•		-		Kennel						
Duplex House		-	•	•	•		g. OTHER: AUTOMOTIVE		1		1	1	1
Courtyard House	-	•			•		Gasoline						
Sideyard House							Automobile Service						-
Cottage		•	•				Truck Maintenance						
House	-	-	•				Drive-Through Facility						
Accessory Unit							Rest Stop						-
b. LODGING						ı	Roadside Stand						
Hotel (no room limit)				•	•	•	Billboard Shanning Contact						
Inn (up to 12 rooms)					•	-	Shopping Center						-
Bed & Breakfast (up to 5 rooms) S.R.O. Hostel			•		•	•	Shopping Mall						
							h. OTHER: CIVIL SUPPORT						
School Dormitory							Fire Station						-
c. OFFICE		1	1	1	1	1	Police Station						
Office Building				-	-	•	Cemetery					-	
Office Use in House					•	•	Funeral Home						-
Live/Work Unit							Hospital Madical Clinia						
d. RETAIL						ı	Medical Clinic						
Open-Market Building		•	-	-	-	-	i. OTHER: EDUCATION			1			
Retail Use in House			•		-		College						
Retail Building				•	-	-	High School						
Display Gallery		-	•	•	-	-	Trade School						
Restaurant					•	•	Elementary School						-
Kiosk							Other - Childcare Center						
Push Cart							j. OTHER: INDUSTRIAL		1		1	1	1
Liquor Selling Establishment							Heavy Industrial Facility						
Special Services							Light Industrial Facility						
Adult Entertainment							Truck Depot					-	
e. CIVIC		1	ı	ı	1	ı	Laboratory Facility						
Bus Shelter	-	-	•	•	•	•	Water Supply Facility						-
Convention Center						•	Sewer and Waste Facility					-	
Conference Center					-	•	Electric Substation						
Exhibition Center					-	•	Wireless Transmitter					-	
Fountain or Public Art							Cremation Facility						
Library		•	•	-		•	Warehouse						
Live Theater				-	•	•	Produce Storage						
Movie Theater				-		•	Mini-Storage						
Museum						•							
Outdoor Auditorium	-	-			-	•			חיי טיכי	ıT			
Parking Structure		<u> </u>				•		•	BY RIGH				
Passenger Terminal		<u> </u>				•			BY WAR	KKANI			
Playground	-	-		•	-	•							
Sports Stadium	-												
Surface Parking Lot	<u> </u>	 				•							
Religious Assembly			•										




SC52 Revised June 2014




Revised June 2014 SC53

ARTICLE 3



SC54 Revised June 2014



I. BUILDING FUNCTION (See Table 10 & Table 12)

Residential	restricted use
Lodging	restricted use
Office	restricted use
Retail	restricted use

k. BUILDING CONFIGURATION (See Table 8)

Principal Building	2 Stories max.
Outbuilding	2 Stories max.

f. LOT OCCUPATION [See Table 14(f)]

Lot Width	68 ft. min. 120 ft. max.
Lot Coverage	50% max.

i. BUILDING DISPOSITION (See Table 9)

Edgeyard	permitted
Sideyard	not permitted
Rearyard	not permitted
Courtyard	not permitted

g. SETBACKS - PRINCIPAL BUILDING [See Table 14(g)]

(g.1) Front Setback Principal	24 ft. min.
(g.2) Front Setback Secondary	20 ft. min.
(g.3) Side Setback	18 ft. min. total
(g.4) Rear Setback	24 ft. min.
Frontage Buildout	50% min. at Setback

h. SETBACKS - OUTBUILDING [See Table 14(h)]

	()2
(h.1) Front Setback	20 ft. min. + bldg. Setback
(h.2) Side Setback	3 ft. or 6 ft. at corner
(h.3) Rear Setback	3 ft. min.

j. PRIVATE FRONTAGES (See Table 7)

Common Lawn	permitted
Porch & Fence	permitted
Terrace or Lightwell	not permitted
Forecourt	not permitted
Stoop	not permitted
Shopfront & Awning	not permitted
Gallery	not permitted
Arcade	not permitted
	D. C I. C T. I.I. 14


Refer to Summary Table 14

PARKING PROVISIONS

(See Table 10 & Table 11)


BUILDING CONFIGURATION

- Building height shall be measured in number of Stories, excluding Attics and raised basements.
- Stories may not exceed 14 feet in height from finished floor to finished ceiling.
- 3. Height shall be measured to the eave or roof deck as specified on Table 8.




SETBACKS - PRINCIPAL BLDG.

- The Facades and Elevations of Principal Buildings shall be distanced from the Lot lines as shown.
- Facades shall be built along the Principal Frontage to the minimum specified width in the table.




SETBACKS - OUTBUILDING


 The Elevations of the Outbuilding shall be distanced from the Lot lines as shown.



PARKING PLACEMENT

- Uncovered parking spaces may be provided within the Second and Third Layer as shown in the diagram [see Table 17(d)].
- Covered parking shall be provided within the Third Layer as shown in the diagram [see Table 17(d)]. Side- or rearentry garages may be allowed in the First or Second Layer by Warrant.
- 3. Trash containers shall be stored within the Third Layer.





I. BUILDING FUNCTION (See Table 10 & Table 12)

Residential	limited use
Lodging	limited use
Office	limited use
Retail	limited use

k. BUILDING CONFIGURATION (See Table 8)

Principal Building	3 Stories max., 2 min.
Outbuilding	2 Stories max.

f. LOT OCCUPATION [See Table 14(f)]

Lot Width	22 ft. min. 96 ft. max.
Lot Coverage	75% max.

i. BUILDING DISPOSITION (See Table 9)

Edgeyard	permitted
Sideyard	permitted
Rearyard	permitted
Courtyard	not permitted

g. SETBACKS - PRINCIPAL BUILDING [See Table 14(g)]

(g.1) Front Setback Principal	20 ft. max.
(g.2) Front Setback Secondary	12 ft. max.
(g.3) Side Setback	0 ft. min., 8 ft. total max.
(g.4) Rear Setback	3 ft. min.
Frontage Buildout	70% min. at Setback

h. SETBACKS - OUTBUILDING [See Table 14(h)]

	. , -
(h.1) Front Setback	20 ft. min. + bldg. Setback
(h.2) Side Setback	0 ft. min. or 3 ft. at corner
(h.3) Rear Setback	3 ft. min.

j. PRIVATE FRONTAGES (See Table 7)


Common Lawn	not permitted
Porch & Fence	permitted
Terrace or Lightwell	permitted
Forecourt	permitted
Stoop	permitted
Shopfront & Awning	permitted
Gallery	permitted
Arcade	not permitted
	Refer to Summary Table 14

PARKING PROVISIONS

(See Table 10 & Table 11)


BUILDING CONFIGURATION

- Building height shall be measured in number of Stories, excluding Attics and raised basements.
- Stories may not exceed 14 feet in height from finished floor to finished ceiling, except for a first floor Commercial Function which must be a minimum of 11 ft. with a maximum of 25 ft.
- 3. Height shall be measured to the eave or roof deck as specified on Table 8.




SETBACKS - PRINCIPAL BLDG.

- The Facades and Elevations of Principal Buildings shall be distanced from the Lot lines as shown.
- Facades shall be built along the Principal Frontage to the minimum specified width in the table.




SETBACKS - OUTBUILDING

 The Elevations of the Outbuilding shall be distanced from the Lot lines as shown.




PARKING PLACEMENT

- All parking areas and garages shall be located at the Second or Third Layer [see Table 17(d)].
- 2. Trash containers shall be stored within the Third Layer.



SC56 Revised June 2014



I. BUILDING FUNCTION (See Table 10 & Table 12)

open use
open use
open use
open use

k. BUILDING CONFIGURATION (See Table 8)

Principal Building	3 Stories max., 2 min.*
Outbuilding	2 Stories max.

f. LOT OCCUPATION [See Table 14(f)]

Lot Width	22 ft. min. 300 ft. max.
Lot Coverage	90% max.**

i. BUILDING DISPOSITION (See Table 9)

Edgeyard	not permitted
Sideyard	permitted
Rearyard	permitted
Courtyard	permitted

g. SETBACKS - PRINCIPAL BUILDING [See Table 14(g)]

(g.1) Front Setback Principal	12 ft. max.
(g.2) Front Setback Secondary	2 ft. min., 12 ft. max.
(g.3) Side Setback	0 ft. min., 24 ft. max.
(g.4) Rear Setback	3 ft. min.
Frontage Buildout	80% min. at Setback

h. SETBACKS - OUTBUILDING [See Table 14(h)]

(h.1) Front Setback	40 ft. max. from rear prop.
(h.2) Side Setback	0 ft. min.
(h.3) Rear Setback	3 ft. max.

j. PRIVATE FRONTAGES (See Table 7)

Common Lawn	not permitted
Porch & Fence	not permitted
Terrace or Lightwell	permitted
Forecourt	permitted
Stoop	permitted
Shopfront & Awning	permitted
Gallery	permitted
Arcade	not permitted
	D. C t. C T. I.I. 14


Refer to Summary Table 14

PARKING PROVISIONS

(See Table 10 & Table 11)


BUILDING CONFIGURATION

- Building height shall be measured in number of Stories, excluding Attics and raised basements.
- Stories may not exceed 14 feet in height from finished floor to finished ceiling, except for a first floor Commercial Function which must be a minimum of 11 ft. with a maximum of 25 ft.
- Height shall be measured to the eave or roof deck as specified on Table 8.
- 4. Expression Lines shall be as shown on Table 8.




SETBACKS - PRINCIPAL BLDG.

- The Facades and Elevations of Principal Buildings shall be distanced from the Lot lines as shown.
- Facades shall be built along the Principal Frontage to the minimum specified width in the table




SETBACKS - OUTBUILDING

 The Elevations of the Outbuilding shall be distanced from the Lot lines as shown.




PARKING PLACEMENT

- All parking Lots, garages, and parking structures shall be located at the Second or Third Layer [see Table 17(d)].
- 2. Trash containers shall be stored within the Third Layer.



^{* 4} permitted by Warrant

^{**} May be allocated per block rather than per lot.



(See Table 1A)

I. BUILDING FUNCTION (See Table 10 & Table 12A)

Delibrite i diteriori (esse rabie re a rabie 12.1)	
Residential	NA
Lodging	NA
Office	NA
Retail	NA

k. BUILDING CONFIGURATION (See Table 8)

Principal Building	2 Stories max.
Outbuilding	2 Stories max.

f. LOT OCCUPATION [See Table 14A(f)]

Lot Width	80 ft. min. 160 ft. max.
Lot Coverage	60% max.

i. BUILDING DISPOSITION (See Table 9)

Edgeyard	permitted
Sideyard	not permitted
Rearyard	not permitted
Courtyard	not permitted

g. SETBACKS - PRINCIPAL BUILDING [See Table 14A(q)]

(g.1) Front Setback Principal	15 ft. min., 25 ft. max.
(g.2) Front Setback Secondary	15 ft. min., 25 ft. max.
(g.3) Side Setback	5 ft. min.
(g.4) Rear Setback	5 ft. min.
Frontage Buildout	50% min. at Setback

h. SETBACKS - OUTBUILDING [See Table 14A(h)]


(h.1) Front Setback	20 ft. min. + bldg. Setback
(h.2) Side Setback	5 ft. or 6 ft. at corner
(h.3) Rear Setback	3 ft. min.

j. PRIVATE FRONTAGES (See Table 7)

Common Lawn	not permitted
Porch & Fence	permitted
Terrace or Lightwell	not permitted
Forecourt	not permitted
Stoop	not permitted
Shopfront & Awning	not permitted
Gallery	not permitted
Arcade	not permitted
	Refer to Summary Table 14A


BUILDING CONFIGURATION

- Building height shall be measured in number of Stories, excluding Attics and raised basements.
- Stories may not exceed 14 feet in height from finished floor to finished ceiling.
- 3. Height shall be measured to the eave or roof deck as specified on Table 8.




SETBACKS - PRINCIPAL BLDG.

- The Facades and Elevations of Principal Buildings shall be distanced from the Lot lines as shown.
- Facades shall be built along the Principal Frontage to the minimum specified width in the table




SETBACKS - OUTBUILDING

 The Elevations of the Outbuilding shall be distanced from the Lot lines as shown.




PARKING PLACEMENT

- All parking areas and garages shall be located at the Second or Third Layer [see Table 17(d)].
- 2. Trash containers shall be stored within the Third Layer.



SC58 Revised June 2014



(See Table 1A)

I. BUILDING FUNCTION (See Table 10 & Table 12A)

Residential	NA
Lodging	NA
Office	NA
Retail	NA

k. BUILDING CONFIGURATION (See Table 8)

Principal Building	3 Stories max.*
Outbuilding	2 Stories max.

f. LOT OCCUPATION [See Table 14A(f)]

Lot Width	20 ft. min. 100 ft. max.
Lot Coverage	80% max.

i. BUILDING DISPOSITION (See Table 9)

Edgeyard	permitted
Sideyard	permitted
Rearyard	permitted
Courtyard	not permitted

g. SETBACKS - PRINCIPAL BUILDING [See Table 14A(g)]

(g.1) Front Setback Principal	5 ft. min., 15 ft. max.
(g.2) Front Setback Secondary	5 ft. min., 15 ft. max.
(g.3) Side Setback	0 ft.
(g.4) Rear Setback	5 ft. min.
Frontage Buildout	70% min. at Setback

h. SETBACKS - OUTBUILDING [See Table 14A(h)]

	. ,-
(h.1) Front Setback	20 ft. min. + bldg. Setback
(h.2) Side Setback	0 ft. min. or 3 ft. at corner
(h.3) Rear Setback	3 ft. min.


j. PRIVATE FRONTAGES (See Table 7)

Common Lawn	not permitted
Porch & Fence	not permitted
Terrace or Lightwell	permitted
Forecourt	permitted
Stoop	permitted
Shopfront & Awning	permitted
Gallery	permitted
Arcade	not permitted
_	Refer to Summary Table 14A

^{* 2} Stories max. if adjacent to existing single-family Residential uses.


BUILDING CONFIGURATION

- Building height shall be measured in number of Stories, excluding Attics and raised basements.
- Stories may not exceed 14 feet in height from finished floor to finished ceiling, except for a first floor Commercial
 Function which must be a minimum of 11 ft. with a maximum of 25 ft.
- 3. Height shall be measured to the eave or roof deck as specified on Table 8.




SETBACKS - PRINCIPAL BLDG.

- The Facades and Elevations of Principal Buildings shall be distanced from the Lot lines as shown.
- Facades shall be built along the Principal Frontage to the minimum specified width in the table.




SETBACKS - OUTBUILDING


 The Elevations of the Outbuilding shall be distanced from the Lot lines as shown.



PARKING PLACEMENT

- All parking Lots, garages, and parking structures shall be located at the Second or Third Layer [see Table 17(d)].
- 2. Trash containers shall be stored within the Third Layer.





(See i

I. BUILDING FUNCTION (See Table 10 & Table 12A)

Residential	NA
Lodging	NA
Office	NA
Retail	NA

k. BUILDING CONFIGURATION (See Table 8)

Principal Building	2 Stories max.
Outbuilding	2 Stories max.

f. LOT OCCUPATION [See Table 14A(f)]

Lot Width	40 ft. min. 80 ft. max.
Lot Coverage	60% max.

i. BUILDING DISPOSITION (See Table 9)

Edgeyard	permitted
Sideyard	not permitted
Rearyard	not permitted
Courtyard	not permitted

g. SETBACKS - PRINCIPAL BUILDING [See Table 14A(q)]

(g.1) Front Setback Principal	10 ft. min., 25 ft. max.
(g.2) Front Setback Secondary	10 ft. min., 25 ft. max.
(g.3) Side Setback	5 ft. min.
(g.4) Rear Setback	5 ft. min.
Frontage Buildout	50% min. at Setback

h. SETBACKS - OUTBUILDING [See Table 14A(h)]


(h.1) Front Setback	20 ft. min. + bldg. Setback
(h.2) Side Setback	0 ft.
(h.3) Rear Setback	3 ft. min.

j. PRIVATE FRONTAGES (See Table 7)

,	,
Common Lawn	not permitted
Porch & Fence	permitted
Terrace or Lightwell	permitted
Forecourt	permitted
Stoop	permitted
Shopfront & Awning	not permitted
Gallery	not permitted
Arcade	not permitted
	Refer to Summary Table 14A


BUILDING CONFIGURATION

- Building height shall be measured in number of Stories, excluding Attics and raised basements.
- Stories may not exceed 14 feet in height from finished floor to finished ceiling.
- 3. Height shall be measured to the eave or roof deck as specified on Table 8.




SETBACKS - PRINCIPAL BLDG.

- The Facades and Elevations of Principal Buildings shall be distanced from the Lot lines as shown.
- Facades shall be built along the Principal Frontage to the minimum specified width in the table




SETBACKS - OUTBUILDING

 The Elevations of the Outbuilding shall be distanced from the Lot lines as shown.




PARKING PLACEMENT

- All parking areas and garages shall be located at the Second or Third Layer [see Table 17(d)].
- 2. Trash containers shall be stored within the Third Layer.



SC60 Revised June 2014



(See Table 1A)

I. BUILDING FUNCTION (See Table 10 & Table 12A)

NA
NA
NA
NA

k. BUILDING CONFIGURATION (See Table 8)

Principal Building	2 Stories max.
Outbuilding	2 Stories max.

f. LOT OCCUPATION [See Table 14A(f)]

Lot Width	18 ft. min. 96 ft. max.
Lot Coverage	90% max.

i. BUILDING DISPOSITION (See Table 9)

Edgeyard	not permitted
Sideyard	not permitted
Rearyard	permitted
Courtyard	not permitted

g. SETBACKS - PRINCIPAL BUILDING [See Table 14A(g)]

(g.1) Front Setback Principal	0 ft. min., 10 ft. max.
(g.2) Front Setback Secondary	0 ft. min., 10 ft. max.
(g.3) Side Setback	0 ft.
(g.4) Rear Setback	0 ft. min.
Frontage Buildout	80% min. at Setback

h. SETBACKS - OUTBUILDING [See Table 14A(h)]


	. ,-
(h.1) Front Setback	40 ft. min. from rear prop.
(h.2) Side Setback	0 ft. min. or 3 ft. at corner
(h.3) Rear Setback	3 ft. max.

j. PRIVATE FRONTAGES (See Table 7)

Common Lawn	not permitted
Porch & Fence	not permitted
Terrace or Lightwell	not permitted
Forecourt	permitted
Stoop	permitted
Shopfront & Awning	permitted
Gallery	permitted
Arcade	not permitted
	Refer to Summary Table 14A


BUILDING CONFIGURATION

- Building height shall be measured in number of Stories, excluding Attics and raised basements.
- Stories may not exceed 14 feet in height from finished floor to finished ceiling, except for a first floor Commercial Function which must be a minimum of 11 ft. with a maximum of 25 ft.
- 3. Height shall be measured to the eave or roof deck as specified on Table 8.
- 4. Expression Lines shall be as shown on Table 8.




SETBACKS - PRINCIPAL BLDG.

- The Facades and Elevations of Principal Buildings shall be distanced from the Lot lines as shown.
- Facades shall be built along the Principal Frontage to the minimum specified width in the table.




SETBACKS - OUTBUILDING


 The Elevations of the Outbuilding shall be distanced from the Lot lines as shown.



PARKING PLACEMENT

- All parking Lots, garages, and parking structures shall be located at the Second or Third Layer [see Table 17(d)].
- Trash containers shall be stored within the Third Layer.





(See Table 1A)

I. BUILDING FUNCTION (See Table 10 & Table 12A)

Residential	NA
Lodging	NA
Office	NA
Retail	NA

k. BUILDING CONFIGURATION (See Table 8)

Principal Building	5 Stories max.(6 by Warrant), 2 min.
Outbuilding	NA

f. LOT OCCUPATION [See Table 14A(f)]

Lot Width	18 ft. min. 400 ft. max.
Lot Coverage	95% max.

i. BUILDING DISPOSITION (See Table 9)

Edgeyard	not permitted
Sideyard	permitted
Rearyard	permitted
Courtyard	permitted

g. SETBACKS - PRINCIPAL BUILDING [See Table 14A(g)]

	- 107-
(g.1) Front Setback Principal	0 ft. min., 10 ft. max.
(g.2) Front Setback Secondary	0 ft. min., 10 ft. max.
(g.3) Side Setback	0 ft. min., 24 ft. max.
(g.4) Rear Setback	0 ft. min.
Frontage Buildout	80% min. at Setback

h. SETBACKS - OUTBUILDING [See Table 14A(h)]


(h.1) Front Setback	NA
(h.2) Side Setback	NA
(h.3) Rear Setback	NA

j. PRIVATE FRONTAGES (See Table 7)

Common Lawn	not permitted
Porch & Fence	not permitted
Terrace or Lightwell	not permitted
Forecourt	permitted
Stoop	permitted
Shopfront & Awning	permitted
Gallery	permitted
Arcade	not permitted
	Refer to Summary Table 14A


BUILDING CONFIGURATION

- Building height shall be measured in number of Stories, excluding Attics and raised basements.
- Stories may not exceed 14 feet in height from finished floor to finished ceiling, except for a first floor Commercial Function which must be a minimum of 11 ft. with a maximum of 20 ft.
- 3. Height shall be measured to the eave or roof deck as specified on Table 8.
- Stepbacks, Recess Lines, and Extension Lines shall be as shown on Table 8.




SETBACKS - PRINCIPAL BLDG.

- The Facades and Elevations of Principal Buildings shall be distanced from the Lot lines as shown.
- Facades shall be built along the Principal Frontage to the minimum specified width in the table.




PARKING PLACEMENT

- All parking Lots, garages, and parking structures shall be located at the Second and Third Layer [see Table 17(h)]
- 2. Trash containers shall be stored within the Third Layer.



SC62



(See Table 1A)

I. BUILDING FUNCTION (See Table 10 & Table 12A)

Residential	Open
Lodging	Open
Office	Open
Retail	Open

k. BUILDING CONFIGURATION (See Table 8)

Principal Building	2 Stories max., 2 min.
Outbuilding	2 Stories max.

f. LOT OCCUPATION [See Table 14A(f)]

Lot Width	40 ft. min. No max.
Lot Coverage	75% max.

i. BUILDING DISPOSITION (See Table 9)

Edgeyard	permitted
Sideyard	permitted
Rearyard	permitted
Courtyard	by Warrant
Suburban Arterial	permitted

g. SETBACKS - PRINCIPAL BUILDING [See Table 14A(g)]

(g.1) Front Setback Principal	15 ft. min.
(g.2) Front Setback Secondary	15 ft. min.
(g.3) Side Setback	5 ft. min.
(g.4) Rear Setback	0 ft. min.
Frontage Buildout	50% min. at Setback

h. SETBACKS - OUTBUILDING [See Table 14A(h)]


(h.1) Front Setback	20 ft. min.				
(h.2) Side Setback	3 ft. min.				
(h.3) Rear Setback	3 ft. min.				

j. PRIVATE FRONTAGES (See Table 7)

Common Lawn	not permitted
Porch & Fence	not permitted
Terrace or Lightwell	permitted
Forecourt	permitted
Stoop	permitted
Shopfront & Awning	permitted
Gallery	permitted
Arcade	not permitted
	Refer to Summary Table 14A


BUILDING CONFIGURATION

- Building height shall be measured in number of Stories, excluding Attics and raised basements.
- Stories may not exceed 14 feet in height from finished floor to finished ceiling, except for a first floor Commercial Function which must be a minimum of 11 ft. with a maximum of 20 ft.
- 3. Height shall be measured to the eave or roof deck as specified on Table 8.




SETBACKS - PRINCIPAL BLDG.

- The Facades and Elevations of Principal Buildings shall be distanced from the Lot lines as shown.
- Facades shall be built along the Principal Frontage to the minimum specified width in the table



SETBACKS - OUTBUILDING

 The Elevations of the Outbuilding shall be distanced from the Lot lines as shown.



PARKING PLACEMENT

- All parking Lots, garages, and parking structures shall be located at the Second or Third Layer [see Table 17(d)].
- Trash containers shall be stored within the Third Layer.




TABLE 16A: Sustainability - Wind Power. This table prescribes opportunities for the placement of types of wind-powered devices within the Transect.

	T1	T2	Т3	T4	T5	
		-				
		•	•			
\$ \$ \$ \$ \$ \$ \$ \$			•	•	•	
			•	•	•	

SC64 Revised June 2014

TABLE 16B: Sustainability - Solar Energy. This table shows opportunities for the placement of types of solar-powered devices within the Transect.

	T1	T2	T3	T4	T5	
Solar Farm		•				
Roof Moounted Solar Panels			•	•	•	
Public Furniture			•	•	•	

SC65 Revised June 2014

 TABLE 16C: Sustainability - Food Production. This table shows ways of incorporating types of food production along the Transect.

	T1	T2	T3	T4	T5	
[5		ΙZ	15	14	10	
Farm		•				
Agricultural Plots						
		-	•			
Vegetable Garden						
		-	-	•		
Urban Farm						
			•	•	•	
Community Garden		•	•	•	•	
Green Roof						
		•	•	•	•	
Vertical Axis					•	

SC66 Revised June 2014


TABLE 16D: Sustainability - Composting and Recycling. This table shows opportunities for the placement of types of composting and recycling solutions within the Transect.

	T1	T2	T3	T4	T5	SD-A
On-Site Organics Processing		-				•
Self-Drop Collection Systems						
Optional/Competitive Collection						
Mandatory Curbside Collection				•	•	•
Centrallized Composting Systems						•
Smaller Regional Composting		•	•			•
On-Site Processing		•				•
Re-Use Centers		•	•	•	-	•
Recycling Processing Centers		•	•	•	-	•
Once-Used materials Storage		•	•			•
Transfer Stations						
Disposal Facilities						


Hutto, Texas							_	
	E							
	90000 as	2000						
	200							
	3500 60	20000						
						99 -99(99		
	- 1 48 9 88	2830 290			22223 42222			
	7 112328				22			
	T1 NATURAL ZONE	T2 RURAL ZONE	T3 SUB-URBAN	T4 GENERAL	T5 URBAN CENTER	SD SPECIAL		
- DAVING		12	ZONE	URBAN ZONE	ZONE	DISTRICT		
a. PAVING			1	•	1			Cost
Compacted Earth		•					L	\$
Wood Planks	•	•					Н	\$\$\$
Plastic Mesh/Geomat							L	\$
Crushed Stone/Shell		•					M	\$
Cast/Pressed Concrete Paver Block				•			L	\$\$
Grassed Cellular Plastic					•		M	\$\$\$
Grassed Cellular Concrete							M	\$\$\$
Pervious Asphalt							L	\$\$
Asphalt			-		•		ī	\$
-							ì	\$\$
Concrete			•	•	•		_	
Pervious Concrete			•	•	•		L	\$\$
Stamped Asphalt								\$\$\$
Stamped Concrete								\$\$\$
Pea Gravel							М	\$
Stone/Masonry Paving Blocks				•				\$\$\$
Wood Paving Blocks on Concrete				•	•		L	\$\$\$
Asphalt Paving Blocks							М	\$\$
b. CHANNELING								
Natural Creek	•						L	\$
Terracing			•	1		1	М	\$\$
Vegetative Swale	-	-	-				L	\$
Drainage Ditch	-	-	-	 			L	\$
Stone/Rip Rap Channels	-		-	_			L	\$\$
		•					-	
Vegetative/Stone Swale		•	•	•	•		L	\$
Grassed Cellular Plastic								\$\$\$
Grassed Cellular Concrete							_	\$\$\$
Soakway Trench								\$\$\$
Slope Avenue							M	\$\$\$
French Drain							M	\$
Shallow Channel Footpath							L	\$
Concrete Pipe			-		-		L	\$\$
Gutter			-	-			L	\$\$
						-	L	\$
Planting Strip Trench			•	•	•		_	
Masonry Trough				•	•		L	\$\$
Canal								\$\$\$
Sculpted Watercourse							M	\$\$\$
Concrete Trough							L	\$\$
Archimedean Screw							L	\$\$\$
c. STORAGE			1	1	ı			
Irrigation Pond		•					L	\$
Retention Basin w/Sloping Bank							L	\$\$
Retention Basin w/Fence		•					L	\$\$
Retention Hollow				•			M	\$
Detention Pond							L	\$
Vegetative Purification Bed			•					\$\$
Flowing Park			-		-			\$\$
Retention Pond			-	-	-			\$\$
Landscaped Tree Well			-					\$\$
				_	_	-		\$\$\$
Pool/Fountain				-	-			
Undergrad Vault/Pipe/Cistern-Corrugated Metal								\$\$
Undergrad Vault/Pipe/Cistern-Precast Concrete				-	-			\$\$
Undergrnd Vault/Pipe/Cistern-Cast in place Concrete					•			\$\$
Grated Tree Well					•			\$\$
Underground Vault/Pipe/Cistern-Plastic								\$\$\$
Paved Basin		<u></u>	<u> </u>	L	•	<u> </u>	М	\$\$\$
d. FILTRATION						1		4
Wetland/Swamp	•						L	\$
				•	1	1	L	\$\$
Filtration Ponds	-	•						
Filtration Ponds Shallow Marsh		•	•				М	\$
	•						L	\$
Shallow Marsh		•					_	
Shallow Marsh Surface Landscape	•		•	•	•		L	\$
Shallow Marsh Surface Landscape Natural Vegetation Constructed Wetland	•	•		•	•		L L M	\$ \$
Shallow Marsh Surface Landscape Natural Vegetation Constructed Wetland Bio-Retention Swale	•	•	•		•		L L M	\$ \$ \$
Shallow Marsh Surface Landscape Natural Vegetation Constructed Wetland Bio-Retention Swale Purification Biotope	•	•					L L M M H	\$ \$ \$ \$\$
Shallow Marsh Surface Landscape Natural Vegetation Constructed Wetland Bio-Retention Swale Purification Biotope Green Finger	•		-				L L M M H L	\$ \$ \$\$ \$\$ \$\$
Shallow Marsh Surface Landscape Natural Vegetation Constructed Wetland Bio-Retention Swale Purification Biotope Green Finger Roof Garden	•	•					L L M M H L M	\$ \$ \$\$ \$\$ \$\$\$
Shallow Marsh Surface Landscape Natural Vegetation Constructed Wetland Bio-Retention Swale Purtification Biotope Green Finger Roof Garden Rain Garden	•						L L M M H L M M	\$ \$ \$\$ \$\$\$ \$\$\$
Shallow Marsh Surface Landscape Natural Vegetation Constructed Wetland Bio-Retention Swale Purification Biotope Green Finger Roof Garden Rain Garden Detention Pond	•						L M M H L M	\$ \$ \$\$ \$\$ \$\$\$ \$\$\$
Shallow Marsh Surface Landscape Natural Vegetation Constructed Wetland Bio-Retention Swale Purification Biotope Green Finger Roof Garden Rain Garden Detention Pond Grassed Cellular Plastic	•						L L M M H L M M M L M M	\$ \$ \$\$ \$\$\$ \$\$\$ \$\$\$ \$\$\$
Shallow Marsh Surface Landscape Natural Vegetation Constructed Wetland Bio-Retention Swale Purification Biotope Green Finger Roof Garden Rain Garden Detention Pond	•						L L M M H L M M M L M M M	\$ \$ \$\$ \$\$ \$\$\$ \$\$\$

SC68 Revised June 2014


a. THOROUGHFARE & FRONTAGES




b. TURNING RADIUS




c. BUILDING DISPOSITION




d. LOT LAYERS




e. FRONTAGE & LOT LINES



SETBACK DESIGNATIONS



NETWORK-BASED PEDESTRIAN SHED



SC69 Revised June 2014

[BLANK PAGE]

SC70 Revised June 2014

SMARTCODE ARTICLE 7. DEFINITIONS

Hutto, Texas

DEFINITIONS

This Article provides definitions for terms in this Code that are technical in nature or that otherwise may not reflect a common usage of the term. If a term is not defined in this Article, then the DRC shall determine the correct definition. Items in italics refer to *Articles, Sections,* or *Tables* in the SmartCode.

A-Grid: cumulatively, those Thoroughfares that by virtue of their pre-existing pedestrian-supportive qualities, or their future importance to pedestrian connectivity, are held to the highest standards prescribed by this Code. See Old Town Master Plan for streets identified as A-Grid. See also B-Grid. (Syn: primary grid.)

Accessory Building: an Outbuilding with an Accessory Unit.

Accessory Sign: a sign that is not part of the total allowable square footage permitted for the building or facade on which it is placed.

Accessory Unit: an Apartment not greater than 800-square feet sharing ownership and utility connections with a Principal Building; it may or may not be within an Outbuilding. See: Table 10 and Table 17. (Syn: ancillary unit)

Architectural Features: ornamentation or decorative features attached to or protruding from or otherwise accentuating an exterior wall.

Adjusted Pedestrian Shed: a Pedestrian Shed that has been adjusted according to Section 3.2, creating the regulatory boundary of a Community Unit.

Affordable Housing: dwellings consisting of rental or for-sale units that have a rent (including utilities) or mortgage payment typically no more than 30% of the income of families earning no more than 80% of median incomes by family size for the county.

Allee: a regularly spaced and aligned row of trees usually planted along a Thoroughfare or Path (PT).

Alley Sign: a sign used to identify the alley entrance to a building or business.

Apartment: a Residential unit sharing a building and a Lot with other units and/or uses; may be for rent, or for sale as a condominium.

Arcade: a Private Frontage conventional for Retail use wherein the Facade is a colonnade supporting habitable space that overlaps the Sidewalk, while the Facade at Sidewalk level remains at the Frontage Line.

Attached Sign: a sign attached to or applied on and totally supported by a part of the building.

Attic: the interior part of a building contained within a pitched roof structure.

Awning: a rigid roof-like cover extending out from the wall of a building to provide cover over windows or doors, that is supported by the exterior wall of the building, and that may include a type that can be retracted, folded, or collapsed against the face of a supporting building.

Awing Sign: a sign placed directly on top of an awning.

Avenue (AV): a Thoroughfare of high vehicular capacity and low to moderate speed, acting as a short distance connector between urban centers, and usually equipped with a landscaped median.

B-Grid: cumulatively, those Thoroughfares that by virtue of their use, location, or absence of pre-existing pedestrian-supportive qualities, may meet a standard lower than that of the A-Grid. See: **A-Grid.** (Syn: secondary grid.)

BRT: see Bus Rapid Transit.

Backbuilding: a single-Story structure connecting a Principal Building to an Outbuilding. See: Table 17.

Base Density: the number of dwelling units per acre before adjustment for other Functions. See: Density.

Bed and Breakfast: an owner-occupied Lodging type offering 1 to 5 bedrooms, permitted to serve breakfast in the mornings to quests.

Bicycle Lane (BL): a dedicated lane for cycling within a moderate-speed vehicular Thoroughfare, demarcated by striping.

Bicycle Route (BR): a Thoroughfare suitable for the shared use of bicycles and automobiles moving at low speeds.

Bicycle Trail (BT): a bicycle way running independently of a vehicular Thoroughfare.

Bioswale: an extended Rain Garden that may run the length of the block.

ARTICLE 7. DEFINITIONS SMARTCODE

Hutto, Texas

Block: the aggregate of private Lots, Passages, Rear Alleys and Rear Lanes, circumscribed by Thoroughfares.

Block Face: the aggregate of all the building Facades on one side of a Block.

Boulevard (BV): a Thoroughfare designed for high vehicular capacity and moderate speed, traversing an Urbanized area. Boulevards are usually equipped with Slip Roads buffering Sidewalks and buildings.

Brownfield: an area previously used primarily as an industrial site.

Bus Rapid Transit: a rubber tire system with its own right-of-way or dedicated lane along at least 70% of its route, providing transit service that is faster than a regular bus.

By Right: characterizing a proposal or component of a proposal for a Community Plan or Building Scale Plan (Article 3, or Article 5) that complies with the SmartCode and is permitted and processed administratively, without public hearing. See: Warrant and Variance.

Canopy: any non-rigid material such as fabric or flexible plastic that is supported by or stretched over a frame, that is attached to an exterior wall, and that may include a type that can be retracted, folded, or collapsed against the face of a supporting building.

Canopy Sign: a sign that is an integral part of the canopy, which is painted on or applied to the canopy.

CLD or **Clustered Land Development:** a Community Unit type structured by a Standard Pedestrian Shed oriented toward a Common Destination such as a general store, Meeting Hall, schoolhouse, or church. CLD takes the form of a small settlement standing free in the countryside. *See: Table 14.* (Syn: Hamlet, Conservation Land Development, cluster)

Civic: the term defining not-for-profit organizations dedicated to arts, culture, education, recreation, government, transit, and municipal parking.

Civic Building: a building operated by not-for-profit organizations dedicated to arts, culture, education, recreation, government, transit, and municipal parking, or for use approved by the legislative body.

Civic Parking Reserve: Parking Structure or parking lot within a quarter-mile of the site that it serves. See: Section 5.9.2

Civic Space: an outdoor area dedicated for public use. Civic Space types are defined by the combination of certain physical constants including the relationships among their intended use, their size, their landscaping and their Enfronting buildings. *See: Table 13.*

Civic Zone: designation for public sites dedicated for Civic Buildings and Civic Space.

Commercial: the term collectively defining workplace, Office, Retail, and Lodging Functions.

Common Destination: an area of focused community activity, usually defining the approximate center of a Pedestrian Shed. It may include without limitation one or more of the following: a Civic Space, a Civic Building, a Commercial center, or a transit station, and may act as the social center of a neighborhood.

Common Yard: a planted Private Frontage wherein the Facade is set back from the Frontage Line. It is visually continuous with adjacent yards. *See: Table 7.*

Community Unit: a regulatory category defining the physical form, Density, and extent of a settlement. The three Community Unit types addressed in this Code are CLD, TND, and RCD. The TOD Community Unit type may be created by an overlay on TND or RCD.

Configuration: the form of a building, based on its massing, Private Frontage, and height.

Corridor: a lineal geographic system incorporating transportation and/or Greenway trajectories. A transportation Corridor may be a lineal Transect Zone.

Cottage: an Edgeyard Building type. A single-family dwelling, on a regular Lot, often shared with an Accessory Building in the back yard.

Courtyard Building: a building that occupies the boundaries of its Lot while internally defining one or more private patios. *See: Table 9.*

Curb: the edge of the vehicular pavement that may be raised or flush to a Swale. It usually incorporates the drainage system. See: Table 4A and Table 4B.

Density: the number of dwelling units within a standard measure of land area.

SC72 Revised June 2014

SMARTCODE ARTICLE 7. DEFINITIONS

Hutto, Texas

Design Speed: is the velocity at which a Thoroughfare tends to be driven without the constraints of signage or enforcement. There are four ranges of speed: Very Low: (below 20 MPH); Low: (20-25 MPH); Moderate: (25-35 MPH); High: (above 35 MPH). Lane width is determined by desired Design Speed. *See: Table 3A.*

Development Review Committee (DRC): part of the Development Services Department,, the DRC is comprised of a representative from each of the various regulatory agencies that have jurisdiction over the permitting of a project.

Developable Areas: lands other than those in the T1 Natural Zone.

Disposition: the placement of a building on its Lot. See: Table 9 and Table 17.

Dooryard: a Private Frontage type with a shallow Setback and front garden or patio, usually with a low wall at the Frontage Line. *See: Table 7.* (Variant: **Lightwell**, light court.)

DRC: Development Review Committee.

Drive: a Thoroughfare along the boundary between an Urbanized and a natural condition, usually along a waterfront, Park, or promontory. One side has the urban character of a Thoroughfare, with Sidewalk and building, while the other has the qualities of a Road or parkway, with naturalistic planting and rural details.

Driveway: a vehicular lane within a Lot, often leading to a garage. See: Section 5.10.

Edgeyard Building: a building that occupies the center of its Lot with Setbacks on all sides. See: Table 9.

Effective Parking: the amount of parking required for Mixed-Use after adjustment by the Shared Parking Factor. *See: Table 11.*

Effective Turning Radius: the measurement of the inside Turning Radius taking parked cars into account. *See: Table 17.*

Elevation: an exterior wall of a building not along a Frontage Line. See: Table 17. See: Facade.

Encroach: to break the plane of a vertical or horizontal regulatory limit with a structural element, so that it extends into a Setback, into the Public Frontage, or above a height limit.

Encroachment: any structural element that breaks the plane of a vertical or horizontal regulatory limit, extending into a Setback, into the Public Frontage, or above a height limit.

Enfront: to place an element along a Frontage, as in "porches Enfront the Street."

Estate House: an Edgeyard Building type. A single-family dwelling on a very large Lot of rural character, often shared by one or more Accessory Buildings. (Syn: country House, villa)

Expression Line: a line prescribed at a certain level of a building for the major part of the width of a Facade, expressed by a variation in material or by a limited projection such as a molding or balcony. *See: Table 8.* (Syn: transition line)

Extension Line: a line prescribed at a certain level of a building for the major part of the width of a Facade, regulating the maximum height for an Encroachment by an Arcade Frontage. See: Table 8.

Facade: the exterior wall of a building that is set along a Frontage Line. See: Elevation

First Layer: the area between the front property line and the required Setback.

Flex Space Building: a building designed to be versatile, which may be used in combination with Office, research and development, quasi-Retail sales, and including but not limited to industrial, warehouse, and distribution uses.

Forecourt: a Private Frontage wherein a portion of the Facade is close to the Frontage Line and the central portion is set back. *See: Table 7.*

Fortune Teller: shall mean a person who foretells personal futures for remuneration.

Frontage: the area between a building Facade and the vehicular lanes, inclusive of its built and planted components. Frontage is divided into **Private Frontage** and **Public Frontage**. *See: Table 4A and Table 7.*

Frontage Line: a Lot Line bordering a Public Frontage. Facades facing Frontage Lines define the public realm and are therefore more regulated than the Elevations facing other Lot Lines. *See: Table 17.*

Function: the use or uses accommodated by a building and its Lot, categorized as *Restricted, Limited,* or *Open,* according to the intensity of the use. *See: Table 10 and Table 12.*

ARTICLE 7. DEFINITIONS SMARTCODE

Hutto, Texas

Gallery: a Private Frontage conventional for Retail use wherein the Facade is aligned close to the Frontage Line with an attached cantilevered shed or lightweight colonnade overlapping the Sidewalk. *See: Table 7.*

Green: a Civic Space type for unstructured recreation, spatially defined by landscaping rather than building Frontages. See: Table 13.

Green Roof: a roof partially or completely covered with vegetation and soil, or a growing medium, planted over a waterproofing membrane. (Syn: eco-roof, living roof, greenroof)

Greenfield: an area that consists of open or wooded land or farmland that has not been previously developed.

Greenway: an Open Space Corridor in largely natural conditions which may include trails for bicycles and pedestrians.

Greyfield: an area previously used primarily as a parking lot. Shopping centers and shopping malls are typical Greyfield sites. (Variant: Grayfield.)

Hamlet: See CLD. (Syn: cluster, settlement.)

Hanging Sign: a sign attached to the underside of a Canopy, Awning, or other support structure.

Head Shop: shall mean a place of business selling paraphernalia associated with the use of illegal drugs.

Highway: a rural and suburban Thoroughfare of high vehicular speed and capacity. This type is allocated to the more rural Transect Zones (T1, T2 and T3).

Home Occupation: non-Retail Commercial enterprises. The work quarters should be invisible from the Frontage, located either within the House or in an Outbuilding. Permitted activities are defined by the Restricted Office category. *See: Table 10.*

House: an Edgeyard Building type, usually a single-family dwelling on a large Lot, often shared with an Accessory Building in the back yard. (Syn: single.)

Infill: *noun* - new development on land that had been previously developed, including most Greyfield and Brownfield sites and cleared land within Urbanized areas. *verb*- to develop such areas.

Infill RCD: a Community Unit type within an Urbanized, Greyfield, or Brownfield area based on a Long or Linear Pedestrian Shed and consisting of T4 and/or T5 Zones. An Infill RCD is permitted By Right in the G-4 Infill Growth Sector and is regulated by Article 4. See: Section 4.2.3. (Var: downtown.)

Infill TND: a Community Unit type within an Urbanized, Greyfield, or Brownfield area based on a Standard Pedestrian Shed and consisting of T3, T4 and/or T5 Zones. An Infill TND is permitted By Right in the G-4 Infill Growth Sector and is regulated by Article 4. See: Section 4.2.2. (Var: neighborhood.)

Inn: a Lodging type, offering up to 12 bedrooms, permitted to serve breakfast in the mornings to guests. See: Table 10

Intensive Green Roof: characterized by thick soil depths (up to 4'), heavy weights and elaborate plantings that include shrubs and trees. Intensive Green Roofs are usually installed over concrete roof decks to bear the weight. They require considerable maintenance.

Kiosk: a small structure with one or more open sides that is used to sell or promote merchandise or services.

Layer: a range of depth of a Lot within which certain elements are permitted. See: Table 17.

Lightwell: A Private Frontage type that is a below-grade entrance or recess designed to allow light into basements. *See: Table 7.* (Syn: light court.)

Linear Pedestrian Shed: a Pedestrian Shed that is elongated along an important Mixed-Use Corridor such as a main Street. A Linear Pedestrian Shed extends approximately 1/4 mile from each side of the Corridor for the length of its Mixed-Use portion. The resulting area is shaped like a lozenge. It may be used to structure a TND, RCD, Infill TND, or Infill RCD. (Syn: elongated pedestrian shed.)

Liner Building: a building specifically designed to mask a parking lot or a Parking Structure from a Frontage.

Live-Work: a Mixed-Use unit consisting of a Commercial and Residential Function. The Commercial Function may be anywhere in the unit. It is intended to be occupied by a business operator who lives in the same structure that contains the Commercial activity or industry. *See:* **Work-Live.** (Syn.: flexhouse.)

SC74 Revised June 2014

SMARTCODE ARTICLE 7. DEFINITIONS

Hutto, Texas

Lodging: premises available for daily and weekly renting of bedrooms. See: Table 10 and Table 12.

Long Pedestrian Shed: a Pedestrian Shed that is an average 1/2 mile radius or 2640-feet, used when a transit stop (bus or rail) is present or proposed as the Common Destination. A Long Pedestrian Shed represents approximately a ten-minute walk at a leisurely pace. It is applied to structure an RCD Community Unit type. *See:* **Pedestrian Shed.**

Lot: a parcel of land accommodating a building or buildings of unified design. The size of a Lot is controlled by its width in order to determine the grain (i.e., fine grain or coarse grain) of the urban fabric.

Lot Line: the boundary that legally and geometrically demarcates a Lot.

Lot Width: the length of the Principal Frontage Line of a Lot.

Low Profile Sign: a sign with a permanent foundation that is not attached to a building, but is a stand alone sign and which does not exceed 60-square feet in area and 4-feet in height.

Main Civic Space: the primary outdoor gathering place for a community. The Main Civic Space is often, but not always, associated with an important Civic Building.

Manufacturing: premises available for the creation, assemblage and/or repair of artifacts, using table-mounted electrical machinery or artisanal equipment, and including their Retail sale.

Meeting Hall: a building available for gatherings, including conferences, that accommodates at least one room equivalent to a minimum of 10-square feet per projected dwelling unit within the Pedestrian Shed in which it is located.

Mixed-Use: multiple Functions within the same building through superimposition or adjacency, or in multiple buildings by adjacency, or at a proximity determined by Warrant.

Mural: artwork applied to the wall of a building that covers all or substantially all of the wall and depicts a scene or event of natural, social, cultural, or historic significance. Excludes any commercial message.

Mural Sign: artwork applied to the wall of a building that covers all or substantially all of the wall and depicts a scene or event of natural, social, or historic significance in addition to advertising a business. The advertisement of such a sign shall not exceed 25% of the completed mural area.

Net Site Area: all developable land within a site including Thoroughfares but excluding land allocated as Civic Zones.

Network Pedestrian Shed: a Pedestrian Shed adjusted for average walk times along Thoroughfares. This type may be used to structure Infill Community Plans. *See: Table 17.*

Non-Conforming Building: a Non-Conforming Building or structure is one that lawfully existed before enactment of a zoning ordinance or change in zoning regulations and that may be maintained after the effective date of this Code, although it no longer complies with the dimensional (Setbacks, Building Disposition and/or Building Configuration) standards for the building or structure of the newly applicable Code.

Non-Commercial Sign: a work of art or message which is political, religious, or pertaining to point of view, expression, opinion, or idea that contains no reference to the endorsement, advertising of, or promotion of patronage, of a business, commodity, service, entertainment, or attraction that is sold, offered or existing.

Non-Conforming Use: a Non-Conforming Use is a use of land or buildings or both that lawfully existed before enactment of a zoning ordinance or change in zoning regulations and that may be maintained after the effective date of this Code, although it no longer complies with use or Building Function restrictions newly applicable to the area.

Office: premises available for the transaction of general business but excluding Retail, artisanal and Manufacturing uses. *See: Table 10.*

Old Town: the 1911 incorporated geographic area of Hutto including the City of Hutto Co-Op property outline within the historic overlay zone in the UDC.

Old Town Master Plan: is a component element of Hutto's Comprehensive Plan which establishes the vision, goals, objectives, and implementation recommendations for the redevelopment of Hutto's 1911 incorporated geographic area; duly adopted by City Council after community input and deliberation.

ARTICLE 7. DEFINITIONS SMARTCODE

Hutto, Texas

Old Town Regulating Plan: a Zoning Map or set of maps that shows the Transect Zones, Civic Zones, location of Frontages, Special Districts, and Special Requirements applicable to the Old Town area subject to the standards in this Code.

Open Market Building: a permanent freestanding Mixed-Use building, often including open air portions, in which local vendors, farmers, and artists may operate displays and the selling of goods.

Open Space: land intended to remain undeveloped; it may be for Civic Space.

Outbuilding: an Accessory Building, usually located toward the rear of the same Lot as a Principal Building, and sometimes connected to the Principal Building by a Backbuilding. *See: Table 17.*

Park: a Civic Space type that is a natural preserve available for unstructured recreation. See: Table 13.

Parking Structure: a building containing one or more Stories of parking above grade.

Passage (PS): a pedestrian connector, open or roofed, that passes between buildings to provide shortcuts through long Blocks and connect rear parking areas to Frontages.

Path (PT): a pedestrian way traversing a Park or rural area, with landscape matching the contiguous Open Space, ideally connecting directly with the urban Sidewalk network.

Pedestrian Shed: An area that is centered on a Common Destination. Its size is related to average walking distances for the applicable Community Unit type. Pedestrian Sheds are applied to structure Communities. See: Standard, Long, Linear or Network Pedestrian Shed. (Syn: walkshed, walkable catchment.)

Planter: the element of the Public Frontage which accommodates street trees, whether continuous or individual.

Plaza: a Civic Space type designed for Civic purposes and Commercial activities in the more urban Transect Zones, generally paved and spatially defined by building Frontages.

Pole Sign: a free-standing sign, usually double-faced, with visible support structure consisting of a round pole, square tube, or other fabricated member, without any type of secondary support, and with the bottom edge of the sign face positioned where it is six feet or more above finished grade.

Primary Sign: the most dominant sign on the building. This may be a single sign or a combination of signs providing that the total square footage of the Primary Sign or signs does not exceed the total allowable square footage permitted for the facade the sign is to be placed on.

Principal Building: the main building on a Lot, usually located toward the Frontage. See: Table 17.

Principal Entrance: the main point of access for pedestrians into a building.

Principal Frontage: on corner Lots, the Private Frontage designated to bear the address and Principal Entrance to the building, and the measure of minimum Lot Width. Prescriptions for the parking Layers pertain only to the Principal Frontage. Prescriptions for the First Layer pertain to both Frontages of a corner Lot. *See:* **Frontage.**

Private Frontage: the privately held Layer between the Frontage Line and the Principal Building Facade. *See: Table 7 and Table 17.*

Projected Sign: a sign which is supported by an exterior corner of a building.

Public Frontage: the area between the Curb of the vehicular lanes and the Frontage Line. See: Table 4A and Table 4B.

Rain Garden: sunken garden using native plants. Trees may be included.

RCD: see Regional Center Development.

Rear Alley (RA): a vehicular way located to the rear of Lots providing access to service areas, parking, and Outbuildings and containing utility easements. Rear Alleys should be paved from building face to building face, with drainage by inverted crown at the center or with roll Curbs at the edges.

Rear Lane (RL): a vehicular way located to the rear of Lots providing access to service areas, parking, and Outbuildings and containing utility easements. Rear Lanes may be paved lightly to Driveway standards. The streetscape consists of gravel or landscaped edges, has no raised Curb, and is drained by percolation.

Rearyard Building: a building that occupies the full Frontage Line, leaving the rear of the Lot as the sole yard. *See: Table 9.* (Var: Rowhouse, Townhouse, Apartment House)

SC76 Revised June 2014

SMARTCODE ARTICLE 7. DEFINITIONS

Hutto, Texas

Recess Line: a line prescribed for the full width of a Facade, above which there is a Stepback of a minimum distance, such that the height to this line (not the overall building height) effectively defines the enclosure of the Enfronting public space. Var: Extension Line. See: Table 8.

Regional Center: Regional Center Development or RCD.

Regional Center Development (RCD): a Community Unit type structured by a Long Pedestrian Shed or Linear Pedestrian Shed, which may be adjoined without buffers by one or several Standard Pedestrian Sheds, each with the individual Transect Zone requirements of a TND. RCD takes the form of a high-Density Mixed-Use center connected to other centers by transit. See: Table 14. (Var: town center, downtown. Syn: Regional Center)

Regulating Plan: a Zoning Map or set of maps that shows the Transect Zones, Civic Zones, Special Districts if any, and Special Requirements if any, of areas subject to, or potentially subject to, regulation by the SmartCode.

Residential: characterizing premises available for long-term human dwelling.

Retail: characterizing premises available for the sale of merchandise and food service. See: Table 10 and Table 12.

Retail Frontage: Frontage designated on a Regulating Plan that requires or recommends the provision of a Shopfront, encouraging the ground level to be available for Retail use. *See:* **Special Requirements.**

Road (RD): a local, rural and suburban Thoroughfare of low-to-moderate vehicular speed and capacity. This type is allocated to the more rural Transect Zones (T1-T3). *See: Table 3A.*

Rowhouse: a single-family dwelling that shares a party wall with another of the same type and occupies the full Frontage Line. See: Rearyard Building. (Syn: Townhouse)

Rural Boundary Line: the extent of potential urban growth as determined by existing geographical determinants. The Rural Boundary Line is permanent.

Second Layer: 20-foot depth from the front Facade.

Secondary Frontage: on corner Lots, the Private Frontage that is not the Principal Frontage. As it affects the public realm, its First Layer is regulated. *See: Table 17.*

Secondary Sign: a sign that is intended to supplement or compliment the Primary Sign, and is subordinate to the Primary Sign, which is included in the total allowable square footage permitted for the building.

Setback: the area of a Lot measured from the Lot line to a building Facade or Elevation that is maintained clear of permanent structures, with the exception of Encroachments listed in *Section 5.7. See: Table 14g.* (Var. build-to line.)

Shared Parking Factor: an accounting for parking spaces that are available to more than one Function. *See: Table*

Shopfront: a Private Frontage conventional for Retail use, with substantial glazing and an Awning, wherein the Facade is aligned close to the Frontage Line with the building entrance at Sidewalk grade. See: Table 7.

Sidewalk: the paved section of the Public Frontage dedicated exclusively to pedestrian activity.

Sideyard Building: a building that occupies one side of the Lot with a Setback on the other side. This type can be a Single or Twin depending on whether it abuts the neighboring House. *See: Table 9.*

Sign, Billboard: sign not otherwise addressed in this article that is free-standing, attached to, or part of a building, and is an off-premise sign that promotes or advertises ideological expressions and/or commodities or services not being offered on the premises on which the sign is located, and exceeds height and size restrictions for the designated location whether on or off premises.

Slip Road: an outer vehicular lane or lanes of a Thoroughfare, designed for slow speeds while inner lanes carry higher speed traffic, and separated from them by a planted median. (Syn: access lane, service lane)

Specialized Building: a building that is not subject to Residential, Commercial, or Lodging classification. *See: Table 9.*

Special District (SD): an area that, by its intrinsic Function, Disposition, or Configuration, cannot or should not conform to one or more of the normative Community Unit types or Transect Zones specified by the SmartCode. Special Districts may be mapped and regulated at the regional scale or the community scale.

ARTICLE 7. DEFINITIONS SMARTCODE

Hutto, Texas

Special Flood Hazard Area: a designation by the Federal Emergency Management Agency (FEMA) that may include the V (Velocity) Zones and Coastal A Zones where building construction is forbidden, restricted, or contingent upon raising to the Base Flood Elevation.

Special Requirements: provisions of Section 3.9 and Section 5.3 of this Code and/or the associated designations on a Regulating Plan or other map for those provisions.

Special Services: body piercing studio, Fortune Tellers, Head Shop, Tattoo Studio and Title Loan Company as defined in this section, and check-cashing, personal loan services, pawn shops, rent-to-own establishments, and other services as defined in Section 371.003 of the Texas Finance Code, as amended.

Square: a Civic Space type designed for unstructured recreation and Civic purposes, spatially defined by building Frontages and consisting of Paths (PT), lawns and trees, formally disposed. See: Table 13.

Standard Pedestrian Shed: a Pedestrian Shed that is an average 1/4 mile radius or 1320-feet, about the distance of a five-minute walk at a leisurely pace. See: Pedestrian Shed.

Stepback: a building Setback of a specified distance that occurs at a prescribed number of Stories above the ground. *See: Table 8.*

Stoop: a Private Frontage wherein the Facade is aligned close to the Frontage Line with the first Story elevated from the Sidewalk for privacy, with an exterior stair and landing at the entrance. *See: Table 7.*

Story: a habitable level within a building, excluding an Attic or raised basement. See: Table 8.

Street (ST): a local urban Thoroughfare of low speed and capacity. See: Table 4B.

Streetscreen: a free-standing wall built along the Frontage Line, or coplanar with the Facade. It may mask a parking lot from the Thoroughfare, provide privacy to a side yard, and/or strengthen the spatial definition of the public realm. (Syn: streetwall.) See: Section 5.7.5f.

Substantial Modification: alteration to a building that is valued at more than 50% of the replacement cost of the entire building, if new.

Swale: a low or slightly depressed natural area for drainage.

T-zone: Transect Zone.

Tattoo Studio: shall mean a facility as defined in Section 146.001 et. seq. of the Texas Health and Safety Code, as amended.

Terminated Vista: a location at the axial conclusion of a Thoroughfare. A building located at a Terminated Vista designated on a Regulating Plan is required or recommended to be designed in response to the axis.

Third Layer: that portion of the Lot that is not within the First and Second Layers.

Third place: a private building that includes a space conducive to unstructured social gathering. Examples of Third Places include bars, cafés and corner stores.

Thoroughfare: a way for use by vehicular and pedestrian traffic and to provide access to Lots and Open Spaces, consisting of Vehicular Lanes and the Public Frontage. *See: Table 3A and Table 17a.*

Title Loan Company: shall mean a business whose function is to make short-term interim loans collateralized by titles from vehicles, boats or other assets.

TND: Traditional Neighborhood Development, a Community Unit type structured by a Standard Pedestrian Shed oriented toward a Common Destination consisting of a Mixed-Use center or Corridor, and in the form of a medium-sized settlement near a transportation route. *See: Table 14.* (Syn: village. Variant: **Infill TND**, neighborhood.)

TOD: Transit Oriented Development. TOD is created by an overlay on all or part of a TND or RCD, or by designation on a Regional Plan, permitting increased Density to support rail or Bus Rapid Transit (BRT) as set forth in *Section 5.9.2d.*

Townhouse: See Rearyard Building. (Syn: Rowhouse)


SC78 Revised June 2014

SMARTCODE ARTICLE 7. DEFINITIONS


Hutto, Texas

Transect: a cross-section of the environment showing a range of different habitats. The rural-urban Transect of the human environment used in the SmartCode template is divided into six Transect Zones. These zones describe the physical form and character of a place, according to the Density and intensity of its land use and Urbanism.

- **Transect Zone (T-zone):** One of several areas on a Zoning Map regulated by the SmartCode. Transect Zones are administratively similar to the land use zones in conventional codes, except that in addition to the usual building use, Density, height, and Setback requirements, other elements of the intended habitat are integrated, including those of the private Lot and building and Public Frontage. *See: Table 1.*
- **Turning Radius:** the curved edge of a Thoroughfare at an intersection, measured at the inside edge of the vehicular tracking. The smaller the Turning Radius, the smaller the pedestrian crossing distance and the more slowly the vehicle is forced to make the turn. *See: Table 17.*
- **Urban Boundary Line:** the extent of potential urban growth as determined by the projected demographic needs of a region. The Urban Boundary Line may be adjusted from time to time.
- **Urbanism:** collective term for the condition of a compact, Mixed-Use settlement, including the physical form of its development and its environmental, functional, economic, and sociocultural aspects.
- **Urbanized:** generally, developed. Specific to the SmartCode, developed at T3 (Sub-Urban) Density or higher.
- Variance: a ruling that would permit a practice that is not consistent with either a specific provision or the Intent of this Code (Section 1.3). Variances are usually granted by the Zoning Board of Adjustment (ZBA) in a public hearing. See: Section 1.5.
- **Wall Sign:** a sign attached to, painted on, or erected against the wall of a building or structure with the exposed face of the sign in a plane parallel to the face of the wall and not projecting more than nine inches from the face of the wall at any point.
- **Warrant**: a ruling that would permit a practice that is not consistent with a specific provision of this Code, but that is justified by its Intent *(Section 1.3).* Warrants are usually granted administratively by the DRC. *See: Section 1.5.*
- Window Sign: a sign affixed to the interior or exterior of a window or placed immediately behind a windowpane.
- Work-Live: a Mixed-Use unit consisting of a Commercial and Residential Function. It typically has a substantial Commercial component that may accommodate employees and walk-in trade. The unit is intended to Function predominantly as work space with incidental Residential accommodations that meet basic habitability requirements. See: Live-Work. (Syn: Live-With.)
- **Yield:** characterizing a Thoroughfare that has two-way traffic but only one effective travel lane because of parked cars, necessitating slow movement and driver negotiation. Also, characterizing parking on such a Thoroughfare.
- **Zoning Map**: the official map or maps that are part of the zoning ordinance and delineate the boundaries of individual zones and districts. See: **Regulating Plan**.



SmartCode Hutto, Texas Exhibit 1A Regulating Plan-Transect Zones




Old Town Regulating Plan
Transect Zones

Exhibit 1A

THE UNION PACIFIC RAILROAD R.O.W.


SmartCode Hutto, Texas Exhibit 1B Regulating Plan-Special Requirements

Requirements




"commercial frontage" includes retail, office, and lodging frontages.

Recommendations



Heart of Hutto Old Town Boundary



All streets not indicated as comprising the 'A' grid are considered 'B' grid streets.

Exhibit 1B

Old Town Regulating Plan
Special Requirements